



3M 28AWG 彩色排线

详细产品规格 - 请点击 cn.100y.com.tw



1700/26



3302-26
3302/10
3302/34



100Y 编号	厂商编号	说明	制造厂商	Num. Of Cores	Ft./Reel	长度 / 卷	Temp. °C	Cond. Size AWG	UL Style/Flame Class	电压	Pitch(mm)
25782	1700/26	3M_彩色排线	3M	26P	UL-20+105°C CSA-20+80°C	100FT/R	28	20462	UL:300V CSA:150V	1.27	
28638	3302-26	3M 彩色排线	3M	26	100FT/卷		-20°C to +105°C Canada: -20°C to +80°C	28		USA: 300V Canada: 150V EU:50V	1.27
28637	3302/10	3M 彩色排线	3M	10		100FT/卷		28			1.27
28639	3302/34	3M 彩色排线	3M	34	100FT/卷			28			1.27

30AWG 灰色扁平排线



100Y 编号	厂商编号	说明	Num. Of Cores	英尺 / 卷	Temp. °C	Cond. Size AWG	UL Style/Flame Class	电压	Pitch(mm)
29713	HM-068L05000FT	30 AWG 灰色扁平排线	68P	500Ft/152.5M	105	30	UL2678	150V	0.635mm
29714	HM-080L05000FT	30 AWG 灰色扁平排线	80P	500Ft/152.5M	105	30	UL2678	150V	0.635mm
8551	HM-68	30 AWG 灰色扁平排线	68P	100Ft/30.5M	105	30	20080 VW-1	150V	0.635mm

24-28AWG 耐高温排线



TEMP-FLEX

100Y 编号	厂商编号	说明	制造厂商	Num. Of Cores	Ft./Reel	Temp. °C	Cond. Size AWG	UL Style/Flame Class	电压	Pitch(mm)
30436	F2807S-10-050-55	Temp-Flex_耐高温 FEP 排线	Temp-Flex	10P	100Ft/30.5M	200°C	28AWG	20424	300V	0.05"
23651	F2807S-20-050-55	Temp-Flex_耐高温 FEP 排线	Temp-Flex	20P	100Ft/30.5M	200°C	28AWG	20424	300V	0.05"
28390	F2807S-26-050-55	Temp-Flex_耐高温 FEP 排线	Temp-Flex	26P	100Ft/30.5M	200°C	28AWG	20424	300V	0.05"
38156	F2807S-30-050-55	Temp-Flex_耐高温 FEP 排线	Temp-Flex	30P	100Ft/30.5M	200°C	28AWG	20424	300V	0.05"
17306	F2807S-34-050-55	Temp-Flex_耐高温 FEP 排线	Temp-Flex	34P	100Ft/30.5M	200	/28AWG	#20424	300V	0.05"
16800	F2807S-40-050-55	Temp-Flex_耐高温 FEP 排线	Temp-Flex	40P	100Ft/30.5M	200°C	28AWG	20424	300V	0.05"
30439	F2807S-50-050-55	Temp-Flex_耐高温 FEP 排线	Temp-Flex	50P	100Ft/30.5M	200°C	28AWG	20424	300V	0.05"
30441	F2807S-60-060-55	Temp-Flex_耐高温 FEP 排线	Temp-Flex	60P	100Ft/30.5M	200°C	28AWG	20424	300V	0.05"

30-32AWG 耐高温排线



F3207S-100-025-81
F3207S-20-025-81



详细产品规格 - 请点击 cn.100y.com.tw

F3001S-80-025-85
F3001S-68-025-85

TEMP-FLEX

100Y 编号	厂商编号	说明	制造厂商	Ft./Reel	Num. Of Cores	Temp. °C	Cond. Size AWG	UL Style/Flame Class	电压	Pitch(mm)
26830	F3001S-68-025-85	Temp-Flex_耐高温 FEP 排线	Temp-Flex	68P	100Ft/R	-55C~150C	30AWG	#20726	150V	0.025
26832	F3001S-80-025-85	Temp-Flex_耐高温 FEP 排线	Temp-Flex	80P	100Ft/R	-55C~150C	30AWG	#20726	150V	0.025
38484	F3207S-100-025-81	Temp-Flex_耐高温 FEP 排线	Temp-Flex	100Ft/R	100P	-55° C to 200° C	32AWG	UL STYLE 20726		0.025inch
38483	F3207S-20-025-81	Temp-Flex_耐高温 FEP 排线	Temp-Flex	100Ft/R	20P	(-55° C to 200° C)	32AWG	UL STYLE 20726		0.025inch

Audio讯号和MIC线材

声音和影像线材



82-黑 6133-黑
6133-门市商品



OFC单芯-2.0



6129



81-黑



86-黑



87-黑

100Y 编号	厂商编号	说明	长度 / 卷
35358	6129	2 芯单隔离线外径 3mm	60M/R
9149	6133-黑	双芯立体音隔离线 4m/m	70M/卷
13908	6133-黑-门市商品	双芯立体音隔离线 4m/m	70M/卷
38992	81-黑	单音隔离线 3m/m	55M/R
9148	82-黑	双芯立体音隔离线 3m/m	80Y(73.152M)/卷
13914	82-黑	双芯立体音隔离线 3m/m	80Y(73.152M)/卷
9150	86-黑	6m/m MIC 线/单音 黑色软质	80Y(73.152M)/卷
9151	87-黑	6m/m MIC 线/双音 黑色软质	80Y(73.152M)/卷
13907	87-黑	6m/m MIC 线/双音 黑色软质	80Y(73.152M)/卷
34981	OFC 单芯-2.0	OFC 单芯-2.0	

6.0mm 立体麦克风线

结构: (20/0.12*2C)+96/0.11 0
D: 6.0mm
材质: OFC 红、黑、蓝三色
长度: 80Y (73.152M)/R
适用于麦克风线。

二芯单隔离 外径 3mm 黑色 80M/卷