




D10-B2/4.5mm




说明:
 额定电流: 1A
 额定电压: 500VAC (1 Min)
 绝缘电阻: 5000Megohms Min
 接触电阻: 20 Milliohms MAX
 温度范围: -55°C~+105°C

Material:
 Insulator: P.B.T +30% G.F
 Contact: Phosphor Bronze



D26-2.0mm




说明:
 额定电流: 1A
 额定电压: 250VAC (1 Min)
 绝缘电阻: 5000Megohms Min
 接触电阻: 20 Milliohms MAX
 温度范围: -55°C~+105°C

Material:
 Insulator: P.B.T +30% G.F
 Contact: Phosphor Bronze



46-02



说明:
 额定电流: 1A
 额定电压: 250VAC (1 Min)
 绝缘电阻: 5000Megohms Min
 接触电阻: 20 Milliohms MAX
 温度范围: -55°C~+105°C

Material:
 Insulator: P.B.T +30% G.F
 Contact: Phosphor Bronze





D10-B3

D10-B2-1

100Y 编号	厂商编号	说明	全长(mm)	Pitch
17981	46-02	短路 Pin Close Type	6mm	2.54mm
28178	D10-B2-1	Open-短路 Pin	Top Open,黄色 / H:6mm	2.54mm
3516	D10-B2/4.5mm	Open-短路 Pin	Top Open,黑色 / H: 4.5mm	2.54mm
2720	D10-B2/6mm	Open-短路 Pin	Top Open,黑色 / H:6mm	2.54mm
2328	D10-B2/8mm	Open-短路 Pin	Top Open,黑色 / H:8mm	2.54mm
32106	D10-B3	Open-短路 Pin 三连体	Top Open,黑色 / H:6mm	2.0mm
23277	D10-D	2.54mm Jumper	Top Open,Black / H: 13mm	2.54mm
4135	D26-2.0mm	Open-短路 Pin	Top Open,黑色 / 2.0mm	2.0mm

"3001" Series (单排) 无极性黑色2.54mm杜邦超薄连接头和端子




F13

TERMINAL:
 MATERIAL: 0.2T PHOS. BRONZE, BRASS
 PLATING: GOLD OR COPPER, UNDERCOATED, TIN PLATED
 WIRE RANGE: SUITABLE FOR AWG #22~#30
 HOUSING:
 MATERIAL: PBT OR NYLON UL 94V-0, V-2
 WAFER:
 POST: BRASS 0.64(.025") SQUARE PIN, TIN-PLATED
 CIRCUITS: 2-60(SINGLE ROW)
 4-120(DOUBLE ROW)



F15




100Y 编号	厂商编号	说明	Pins	Pitch	Parking
4603	F13-01P	黑色无极性连接头	1P	2.54mm	
3691	F13-02P	黑色无极性连接头	2P	2.54mm	
3690	F13-03P	黑色无极性连接头	3P	2.54mm	
3689	F13-04P	黑色无极性连接头	4P	2.54mm	
4583	F13-05P	黑色无极性连接头	5P	2.54mm	
4584	F13-06P	黑色无极性连接头	6P	2.54mm	
4585	F13-08P	黑色无极性连接头	8P	2.54mm	
4586	F13-10P	黑色无极性连接头	10P	2.54mm	
4587	F13-12P	黑色无极性连接头	12P	2.54mm	
19768	F13-14P	黑色无极性连接头	14P	2.54mm	
23717	F13-20P	黑色无极性连接头	20P	2.54mm	
13706	F15	杜邦超薄 端子漂金	10000/R	2.54mm	10,000 PCS(reel)

详细产品规格 - 请点击 cn.100y.com.tw

"3001" Series (双排) 无极性黑色2.54mm杜邦超薄连接头



F14




TERMINAL:
 MATERIAL: 0.2T PHOS. BRONZE, BRASS
 PLATING: GOLD OR COPPER, UNDERCOATED, TIN PLATED
 WIRE RANGE: SUITABLE FOR AWG #22~#30
 HOUSING:
 MATERIAL: PBT OR NYLON UL 94V-0, V-2
 WAFER:
 POST: BRASS 0.64(.025") SQUARE PIN, TIN-PLATED
 CIRCUITS: 2-60(SINGLE ROW)
 4-120(DOUBLE ROW)

100Y 编号	厂商编号	说明	Pins
4653	F14-10P	无极性接头(双排母座)	10P
4654	F14-12P	无极性接头(双排母座)	12P
4655	F14-14P	无极性接头(双排母座)	14P
4656	F14-16P	无极性接头(双排母座)	16P
4657	F14-18P	无极性接头(双排母座)	18P
4658	F14-20P	无极性接头(双排母座)	20P
15619	F14-30P	无极性接头(双排母座)	30P
16033	F14-34P	无极性接头(双排母座)	34P
15934	F14-40P	无极性接头(双排母座)	40P

2.54mm 单排排针



D12-40P



说明:
 额定电流: 3A
 额定电压: 800VAC (1 Min)
 绝缘电阻: 1000Megohms Min
 接触电阻: 30 Milliohms MAX
 温度范围: -40°C~+85°C

Material:
 Insulator: NYLON-6T(UL 94V-0)
 Contact: Phosphor Bronze
 Plated:
 Underplating: nickel plating for All 80u" ~120u"
 All plating: tin-lead 90/10
 Plating 100u" ~200u"

100Y 编号	厂商编号	说明	Angle	Pins 1 头?	Up(mm)	Down(mm)	全长(mm)
4737	D12-40P	2.54mm 单排排针	90°	1*40	3.0	3.3	9.54

详细产品规格 - 请点击 cn.100y.com.tw

