



2. 54mm端子线



F29-10P/2.54 8P

主要规格

- Insulator material: NYLON 66(UL 94V-O)
- Wire range: AWG#28~#22
- Rated voltage: 250V
- Rated current: 1A
- Contact resistance: $\leq 0.01 \Omega$
- Insulation resistance: $\geq 1000M \Omega$
- Withstanding voltage: 1000V.AC
- Temp range for usage: -25~85°C
- Relative humidity: 93%+40
- P.C board thickness: 1.6mm



I43-XH/D1-450

2.54 母座附线连接器

- 脚距: 2.54mm
- 耐压: AC 250V
- 耐电流: 1A
- 45CM
- 双头白, 黑, 红, 黄, 绿, 灰, 蓝, 咖, 紫



I16-B2-450

2.54 母座附线连接器

- 脚距: 2.54mm
- 耐压: AC 250V
- 耐电流: 1A
- 45CM
- 双头白, 黑, 红, 黄, 绿, 灰, 蓝, 咖, 紫



I50-SH/E1-450_单头

2.54 母座附线连接器

- 脚距: 2.54mm
- 耐压: AC 250V
- 耐电流: 1A
- 45CM
- 双头白, 黑, 红, 黄, 绿, 灰, 蓝, 咖, 紫

详细产品规格 - 请点击cn.100y.com.tw



3194-5

2.54 母座附线连接器

- 脚距: 2.54mm
- 耐压: AC 250V
- 耐电流: 1A (使用 AWG24# 1007 UL线材)
- Pin 数: 5P
- 附线40cm 5003端子线

100Y 编号	厂商编号	说明	Pin
7711	3194-10	2.54mm 5003 端子线 40CM-单边	10P
7706	3194-12	2.54mm 5003 端子线 40CM-单边	12P
7705	3194-2	2.54mm 5003 端子线 40CM-单边	2P
8372	3194-3	2.54mm 5003 端子线 40CM-单边	3P
8373	3194-4	2.54mm 5003 端子线 40CM	4P
12761	3194-5	2.54mm 5003 端子线 40CM	5P
9111	3194-6	2.54mm 5003 端子线 40CM-单边	6P
9112	3194-7	2.54mm 5003 端子线 40CM-单边	7P
9113	3194-8	2.54mm 5003 端子线 40CM-单边	8P
28255	3194-9	5003 端子线	9P
7520	F11-02P-450D	AWG24/45CM 9001 母头+端子线	2P
9141	F11-03P-450D	AWG24/45CM 9001 母头+端子线	3P
10629	F11-04P-450D	AWG24/45CM 9001 母头+端子线	4P
7518	F11-05P-450D	AWG24/45CM 9001 母头+端子线	5P
12059	F11-06P-450D	AWG24/45CM 9001 母头+端子线	6P
9979	F11-07P-450D	AWG24/45CM 9001 母头+端子线	7P
10627	F11-08P-450D	AWG24/45CM 9001 母头+端子线	8P
12058	F11-10P-450D	AWG24/45CM 9001 母头+端子线	10P
14302	F29-10P/2.54 8P	#26 PH10P 穿 8P/2.54 8P 绞线	8P
12420	I16-B1-450	#26 2.54mm 端子线 45CM 单头	
12421	I16-B2-450	#26 2.54mm 端子线 45CM 双头白,黑,红,黄,绿,灰,蓝,咖,紫	
12407	I50-SH/E1-450_单头	#26 杜邦超薄镀金_单头端子线 45CM(白,黑,红,黄,绿,灰,蓝,咖啡色)	
12650	I50-SH/E2-450_双头	#26 杜邦超薄镀金_双头端子线 45CM(白,黑,红,黄,绿,灰,蓝,咖啡色)	

3. 96mm端子线



I17-D1-450

3.96 母座附线连接器 AWG#22

- 脚距: 3.96mm
- 耐压: AC 250V
- 耐电流: 3A (使用 1005 UL线材)
- #22 1005 VH 端子线 45CM 单头



I54-VH-450C/15

3.96 母座附线连接器 AWG#22

- 脚距: 3.96mm
- 耐压: AC 250V
- 耐电流: 3A (使用 1005 UL线材)
- #22 1005 VH 端子线 45CM 单头



F26-02P-300C

TERMINAL

- MATERIAL: 0.25T BRASS
 - PLATING: COPPER-UNDERCOATED, TIN-PLATED
- ### HOUSING
- MATERIAL: NYLON 66, UL 94V-0, V-2 WAFER
 - TOP ENTRY: ATW-04
 - SIDE ENTRY: ATW-04R
 - IDT TYPE: AHT-04
 - WIRE TO WIRE TYPE: AH-04, ARH-04
 - CIRCUITS: 4



3195-2-10CM

3.96 母座附线连接器 AWG#20

- 脚距: 3.96mm
- 耐压: AC 250V
- 耐电流: 3A (使用 AWG20# 1007 UL线材)
- 3.96 7P 40CM(单头)


100Y 编号	厂商编号	说明	插脚
9109	3195-2	3.96mm 端子+线 40CM	2P
28087	3195-2-10CM	3.96mm 端子线	2P
8374	3195-3	3.96mm 端子线 40CM	3P
9108	3195-4	3.96mm 端子线 40CM	4P
8375	3195-5	3.96mm 端子线 40CM	5P
9110	3195-6	3.96mm 端子线 40CM	6P
21979	3195-7	3.96mm 端子线 40CM	7P
16135	F26-02P-300C	#22 5.08mm 30CM 单头	2P
12405	I17-D1-450	#22 3.96mm 端子线 45CM 单头白,黑,红,黄,绿,灰,蓝,咖,紫	
12406	I54-VH-450A	#18 VH 端子线 45CM 单头(白,黑,红,黄,绿,灰,蓝,咖啡)	
13321	I54-VH-450C/15	#22 1015 VH 端子线单头	

6. 35mm端子线



规格说明:

- 额定电流: 10A AC, DC (AWG 14)
- 额定电压: 600V AC, DC
- 承受电压: 5000V AC/Minute
- 接触电阻: 10mΩ Max.
- 绝缘电阻: 1000MΩ Min.
- 温度范围: -55°C to +105°C
- 可适用的电脑板厚度: 1.6mm



详细产品规格 - 请点击cn.100y.com.tw

产品名称	Circuits	Dim.A
Housing 6350F0202	2	13.97

100Y 编号	厂商编号	说明	插脚
22189	M7201006	6350F0202 头 +45CM 线 6.35mm 端子线/2P	2P
22190	M7201007	6350F0202 头 +45CM 线 6.35mm 端子线/3P	3P
22191	M7201008	6350F0202 头 +45CM 线 6.35mm 端子线/4P	4P

