



其它类-连接器

**FCN-3659040-AU**  
Voltage Rating AC 250V  
Contact resistance: 15mΩ max.

**FUJITSU**

详细产品规格 - 请点击 [cn.100y.com.tw](http://cn.100y.com.tw)

**SDAMB-01215BT00**

**K-CFCI-02**  
Cover: sus 304, T=0.3mm  
Heaver: sus 304, T=0.3mm  
Ejector: high temperature plastic UL94V-0 color=black

**KINGFONT**  
You can rely on .....

**CFCMD-35T15W110**

**HR10A-10R-12SB**

**HRS**

**HR10A-10R-10SB**

**HRS**

**HR10A-10R-10PB**

**HRS**

**HR10A-7R-6SB**

**HRS**

**S-1660+1660CA+1660-STA**

**HRS**

**CHM-6021**

**PLT**

**0-0177766-1**

**AMP**

**Other properties:**  
RoHS/ELV compliance History: Always was RoHS compliant  
Insulation Diameter(mm[in]): 1.00-1.90[.039-.075]  
Housing material : nylon  
Contact material : brass  
Contact mating Area plating : tin  
Length(mm[in]): 12.00[0.472]  
Width (mm[in]): 11.00[0.433]  
Height (mm[in]): 7.00[0.275]  
Wire type: thin

100Y 编号	厂商编号	制造厂商	说明	类型	Pins	Parking	插入端/YES	接收端/YES	材质
32107	0-0177766-1	AMP	TAP Cable Connector/Splice	Cable Connector/Splice					Nylon,Bras s
13192	FCN-3659040-AU	FUJITSU	40P 90 度双排连接头	90 度	40P				
14537	CFCMD-35T15W110	KINGFON T	Compact Flash Type II Stand Off 2.0mm Normal Type	0.635mm PITCH	50P				
19491	CHM-6021	PLT	4P 母插头						
19490	CHM-6021A	PLT	4P 公插头						
27741	HR10A-10R-10PB	HRS	CIRCULAR CONNECTOR	Solder Type	10P 公头		NO	YES	
23323	HR10A-10R-10SB	HRS	CIRCULAR CONNECTOR	Solder Type	10P female		NO	YES	
27742	HR10A-10R-12SB	HRS	CIRCULAR CONNECTOR	Solder Type	12P female		NO	YES	
27740	HR10A-7R-6SB	HRS	CIRCULAR CONNECTOR	Solder Type	6P female		NO	YES	
14538	K-CFCI-02		CFCMD-35015W110 之 推杠	CFCMD-35015W110 之 推杠					
12088	S-1660+1660CA+1660-STA		焊线式接头 3 件/一组	1660	60				
15295	SDAMB-01215BT00	KINGFON T	Secure Digital Card Connector Type II	GOLD PLATING 黑色	12Pin				

