





接续和其它类端子+接地片 焊片, 接地片


详细产品规格 - 请点击cn.100y.com.tw




ITIM NO	NAMA TAB		DIMENSION		
	Inch mm	STUD SIZE	W		L
			Inch mm	Inch mm	Inch mm
PC250-836LR	.032 x .250 0.8 x 6.35	#6	.311	7.9	.551 14.0



ITIM NO	NAMA TAB		DIMENSION		
	Inch mm	STUD SIZE	W		L
			Inch mm	Inch mm	Inch mm
PCIL25005LR	.032 x .250 0.8 x 6.35	#6	3.5	.315 8.0	.689 17.5





ITIM NO	DIMENSION	NAMA TAB	W	L
		Inch mm	Inch mm	Inch mm
TWALR	3-WAY ADAPTER (2MALE TAB)	.250 6.35	.291 7.4	.709 18.0



ITIM NO	D1 Inch mm	D2 Inch mm	W1 Inch mm	W2 Inch mm	E Inch mm	L Inch mm
ST-2LT	#1 2.2	.059 1.5	.197 5.0	.122 3.1	.280 7.1	.437 11.1
ST-3LT	#4 3.2	.059 1.5	.248 6.3	.122 3.1	.311 7.9	.500 12.7
ST-3.5LT	#6 3.5	.059 1.5	.248 6.3	.122 3.1	.311 7.9	.500 12.7
ST-4LT	#8 4.3	.059 1.5	.268 6.8	.122 3.1	.311 7.9	.500 12.7
ST-5LT	#10 5.3	.059 1.5	.370 9.4	.169 4.3	.354 9.0	.622 15.8
ST-6LT	1/4 6.4	.059 1.5	.370 9.4	.169 4.3	.354 9.0	.622 15.8

100Y 编号	厂商编号	说明	螺丝口径 d1	L(mm)	W1(mm)	材质
7957	1101	焊片				
28691	PC187(8)LR	Male Terminal		12.7	6.3	镀铜
6494	PC1L25005LR	Male Terminal		17.5	8.0	Brass
6479	PC250-836LR	Male Terminal		14	7.9	镀铜
14071	ST-2LT	2.2mm 焊片	2.2mm	11.1mm	5.0mm	BRASS
14074	ST-3.5LT	3.5mm 焊片	3.5mm	12.7mm	6.3mm	BRASS
14072	ST-3LT	3.2mm 焊片	3.2mm	12.7mm	6.3mm	BRASS
19801	ST-4LT	4.3mm 焊片	4.3mm	12.7mm	6.8mm	BRASS
6452	TWALR	Multi-Way Adapter		18	7.4	Brass Finish



(1000片装)

中接管端子(全Nylon. Vinyl护套)

详细产品规格 - 请点击cn.100y.com.tw




NYLON-INSULATED (FLARED) BUTT SPLICE CONNECTORS
 MAXIMUM ELECTRIC CURRENT:
 22-16A.W.G.: 19 AMPERE
 16-14A.W.G.: 27 AMPERE
 12-10A.W.G.: 48 AMPERE
 MAXIMUM ELECTRICAL RATING:105°C 600 VOLTS MAX.
 CONNECTOR MATERIAL:COPPER TUBULAR



WBNY5 INSULATION MATERIAL: NYLON

INSULATION COLOR:

- 22-16 A.W.G.: RED
- 16-14 A.W.G.: BLUE
- 12-10 A.W.G.: YELLOW



Wire range A. W. G mm ²	ITEM NO	L	DIMENSION Inch mm		
			D	d1	d1
22-16A. W. G. 0.5-1.5mm ²	WBNY 1	1.220	.158	.071	
16-14A. W. G. 1.5-2.5mm ²	WBNY 2	1.220	.181	.098	
12-10A. W. G. 4-6 mm ²	WBNY 5	1.614	.244	.142	
		41.0	6.2	3.6	




NYLON-INSULATED (FLARED) BUTT SPLICE CONNECTORS
 MAXIMUM ELECTRIC CURRENT:
 22-16A.W.G.: 19 AMPERE
 16-14A.W.G.: 27 AMPERE
 12-10A.W.G.: 48 AMPERE
 MAXIMUM ELECTRICAL RATING:105°C 600 VOLTS MAX.
 CONNECTOR MATERIAL:COPPER



BNYF2 INSULATION MATERIAL: NYLON

INSULATION COLOR:

- 22-16 A.W.G.: RED
- 16-14 A.W.G.: BLUE
- 12-10 A.W.G.: YELLOW



Wire range A. W. G mm ²	ITEM NO	L	DIMENSION Inch mm		
			D	d1	d1
22-16A. W. G. 0.5-1.5mm ²	BNYT 1	.992	.157	.067	
16-14A. W. G. 1.5-2.5mm ²	BNYT 2	.992	.177	.091	
12-10A. W. G. 4-6 mm ²	BNYT 5	1.110	.248	.134	
22-16A. W. G. 0.5-1.5 mm ²	BNY 1	.992	.157	.067	
16-14A. W. G. 1.5-2.5 mm ²	BNY 2	.992	.177	.091	
12-10A. W. G. 4-6 mm ²	BNY 5	1.110	.248	.134	

100Y 编号	厂商编号	制造厂商	说明	护套颜色	尺寸 L*d1*D	压接线径	Conn. Material	耐温°C/Volt/A	护套材质
4967	BNYF1	KST	Nylon 中接管端子	红色	25.2*1.7*4	16-22AWG(0.5-1.5mm ²)	Copper	105°C/600V/19A	Nylon
4973	BNYF2	KST	Nylon 中接管端子	蓝色	25.2*2.3*4.5	14-16AWG(1.5-2.5mm ²)	Copper	105°C/600V/27A	Nylon
4976	BNYF5	KST	Nylon 中接管端子	黄色	28*3.4*6.3	12-10AWG(4-6mm ²)	Copper	105°C/600V/48A	Nylon
6460	WBNY1	KST	Nylon 窗型中接管端子	红色	31*1.8*4.0	22-16AWG(0.5-1.5mm ²)	Copper Tubular	105°C/600V/19A	Nylon
6447	WBNY5	KST	Nylon 窗型中接管端子	黄色	41*3.6*6.2	12-10AWG(4-6mm ²)	Copper Tubular	105°C/600V/48A	Nylon

