



接续端子



UY2

- Features:RUS Listed, Full featured
- Operating Temperature:-40~140°C  
-40~285 F
- UL, CSA, or CE Certified:n/a
- Soild wire only




UY

- Features:Moisture resistant seal.
- Operating Temperature:-40~140°C  
-40~285 F
- UL, CSA, or CE Certified:n/a
- Soild wire only



KW-3

- 材质:PP
- 本产品具有中途补助之接线用。
- 使用时, 不须事先剥线, 只要选好位置内压即可。



详细产品规格 - 请点击cn.100y.com.tw

Connector	Type Connector	Special Features	Maximum Insulation O.D		Cable Type	
			Metric (mm)	inches	PIC-unfilled and PIC-filled AWG	Pulp or paper AWG
Butt Splicing UY		Gel-Filled Polycarbonate	1.52	0.060	22-26 0.7-0.4	22-26 0.7-0.4

Connector	Type Connector	Special Features	Maximum Insulation O.D		Cable Type	
			Metric (mm)	inches	PIC-unfilled and PIC-filled AWG	Pulp or paper AWG
Butt Splicing UY2		Gel-Filled Polypropelene RUS Listed	2.08	0.082	19-26 0.9-0.4	N/A N/A



KW-11

- 材质:PP
- 本产品具有中途补助之接线用。
- 使用时, 不须事先剥线, 只要选好位置内压即可。



100Y 编号	厂商编号	制造厂商	说明	适用压接线径	护套颜色	Package	护套材质
35131	KW-11	KSS	接线夹	16-14AWG	蓝色	100 个/包	PP
15893	KW-3		接线夹	18-22AWG(1.25mm <sup>2</sup> )	Red	100 个/包	PP
14305	KW-4	KSS	接线夹	18-14AWG(2mm <sup>2</sup> )	Blue	100 个/包	PP
13729	KW-5	KSS	接线夹	12-10AWG(5.5mm <sup>2</sup> )	Yellow	100 个/包	PP
8266	UY	3M	UY 端子/通讯电话用	22-26AWG		(100 个/Box)	
14980	UY2	3M	UY2 通讯电话用	19-26AWG(0.9-0.4mm)Solid wire		(100 个/Box)	

压线用端子和工具  
针型压线端子(Vinyl, Nylon护套)



NYLON-INSULATED PIN TERMINALS


- MAXIMUM ELECTRIC CURRENT:
- 26-22 A.W.G.: 9 AMPERE
- 22-16 A.W.G.: 19 AMPERE
- 16-14 A.W.G.: 27 AMPERE
- 12-10 A.W.G.: 48 AMPERE

MAXIMUM ELECTRICAL RATING:105°C 600 VOLTS MAX.

CONNECTOR MATERIAL:NYLON

INSULATION COLOR:

- 26-22 A.W.G.:YELLOW
- 22-16 A.W.G.:RED
- 16-14 A.W.G.:BLUE
- 12-10 A.W.G.:YELLOW



Wire range A. W. G mm <sup>2</sup>	BRAZED SEAM	ITEM NO	BUTTED SEAM	W	F	DIMENSION		Inch	mm	d1	T
						L	E				
26-22A.W.G. 0.2-0.5mm <sup>2</sup>		PTV0.5-9	PTV0.5-9	0.055	.394	.709	.315	.087	.039	.020	
				1.4	10.0	18.0	8.0	2.2	1.0	0.5	
		PTVB1-9	PTV1-9		.354	.740					
					9.0	18.8					
22-16A.W.G. 0.5-1.5mm <sup>2</sup>		PTVB1-10	PTV1-10		.394	.780					
					10.0	19.8					
		PTVB1-12	PTV1-12	0.75	.472	.858	.394	.157	.067	.030	
				1.9	12.0	21.8	10.0	4.0	1.7	0.75	
		PTVB1-13	PTV1-13		.512	.898					
					13.0	22.8					
		PTVB1-14	PTV1-14		.551	.937					
					14.0	23.8					
	PTVB1-16	PTV1-16		.630	1.016						
				16.0	25.8						



NYLON-INSULATED PIN TERMINALS


- MAXIMUM ELECTRIC CURRENT:
- 26-22 A.W.G.: 9 AMPERE
- 22-16 A.W.G.: 19 AMPERE
- 16-14 A.W.G.: 27 AMPERE
- 12-10 A.W.G.: 48 AMPERE

MAXIMUM ELECTRICAL RATING:105°C600 VOLTS MAX.

CONNECTOR MATERIAL:NYLON

INSULATION COLOR:

- 26-22 A.W.G.:YELLOW
- 22-16 A.W.G.:RED
- 16-14 A.W.G.:BLUE
- 12-10 A.W.G.:YELLOW



Wire range A. W. G mm <sup>2</sup>	BRAZED SEAM	ITEM NO	BUTTED SEAM	W	F	DIMENSION		Inch	mm	d1	T
						L	E				
12-10A.W.G. 4-6mm <sup>2</sup>		PTNB5-13	PTV0.5-9	.100	.551	1.063	.512	.248	.134	.039	
				2.8	14.0	27.0	13.0	6.3	3.4	1.0	
16-14A.W.G. 1.5-2.5mm <sup>2</sup>		PTVB2-9	PTV2-9		.354	.740					
					9.0	18.8					
		PTVB2-10	PTV2-10		.394	.780					
					10.0	19.8					
		PTVB2-12	PTV2-12	0.75	.472	.858	.394	.177	.091	.031	
				1.9	12.0	21.8	10.0	4.5	2.3	0.8	
	PTVB2-13	PTV2-13		.512	.898						
				13.0	22.8						
	PTVB2-16	PTV2-16		.630	1.024						
				16.0	26.0						

100Y 编号	厂商编号	制造厂商	说明	护套颜色	尺寸 L	压接线径 d	护套材质	耐温°C/Volt/A
6462	PTNY0.5-9	KST	针型端子	黄色	18L*1.0d1*2.2D	26-22AWG(0.2~0.5mm <sup>2</sup> )	Nylon	105°C/600V
29757	PTNY5-13	KST	针型端子	黄色	27L*3.4d1*6.4D	12-10AWG(4~6mm <sup>2</sup> )	Nylon	105°C/600V
4272	PTV1-10	KST	VINYL 护套针型端子	RED	19.8mm	22-16AWG 0.5-1.5mm <sup>2</sup>	VINYL	75°C
11871	PTV1-12	KST	VINYL 护套针型端子	红色	21.8mm	22-16AWG 0.5-1.5mm <sup>2</sup>	VINYL	75°C
7761	PTV2-10	KST	VINYL 护套针型端子	BLUE	19.8mm	16-14 AWG 1.5-2.5mm <sup>2</sup>	VINYL	75°C
11870	PTV2-12	KST	VINYL 护套针型端子	蓝色	21.8mm	16-14AWG 1.5-2.5mm <sup>2</sup>	VINYL	75°C
8298	PTV5-13	KST	VINYL 护套针型端子	黄色	27mm	4-6mm <sup>2</sup> (12~10AWG)	Vinyl	75°C

