




子弹型公/母压线端子 (Vinyl, Nylon护套)

详细产品规格 - 请点击cn.100y.com.tw




**VINYL-FULLY INSULATED RECEPTACLE DISCONNECTORS**  
**KST**  
 MAXIMUM ELECTRIC CURRENT:  
 22~16 A.W.G.:10 AMPERE  
 16~14 A.W.G.:15 AMPERE  
 12~10 A.W.G.:24 AMPERE  
 MAXIMUM ELECTRICAL RATING:75°C 300 VOLTS MAX.  
 INSULATION MATERIAL: VINYL  
 TERMINAL MATERIAL: BRASS  
 INSULATION COLOR:  
 22-16 A.W.G.:RED  
 16-14 A.W.G.:BLUE  
 12-10 A.W.G.:YELLOW  
 TERMINAL BARREL I.D.:  
 22-16 A.W.G.: C=1.7mm  
 16-14 A.W.G.: C=2.3mm



Wire range	A. W. G mm <sup>2</sup>	ITEM NO	W	F	L	B	D	T
22-16A.W.G. 0.5-1.5mm <sup>2</sup>	.153 3.9	FRV1-156	.287	.906	.413	.157	.016	
			7.3	23.0	10.5	4.0	0.4	
16-14A.W.G. 1.5-2.5mm <sup>2</sup>	.153 3.9	FRV2-156	.287	.925				
			7.3	23.5	4.13	.177	.016	
16-14A.W.G. 1.5-2.5mm <sup>2</sup>	.193 4.9	FRV2-195	.276	.965	10.5	4.5	0.4	
			7.0	23.5				
16-14A.W.G. 1.5-2.5mm <sup>2</sup>	.193 4.9	FRV2-195	.276	.945	.492	.217	.018	
			7.0	24.0	12.5	5.5	0.45	




**NYLON-FULLY INSULATED BULLET DISCONNECTORS**  
**KST**  
 MAXIMUM ELECTRIC CURRENT:  
 22~16 A.W.G.:10 AMPERE  
 16~14 A.W.G.:15 AMPERE  
 MAXIMUM ELECTRICAL RATING:105°C 300 VOLTS MAX.  
 INSULATION MATERIAL: NYLON  
 TERMINAL MATERIAL: BRASS  
 INSULATION COLOR:  
 22-16 A.W.G.:RED  
 16-14 A.W.G.:BLUE  
 TERMINAL BARREL I.D.:  
 22-16 A.W.G.: C=1.7mm  
 16-14 A.W.G.: C=2.3mm



Wire range	A. W. G mm <sup>2</sup>	ITEM NO	W	F	L	B	D	T
22-16A.W.G. 0.5-1.5mm <sup>2</sup>	.157 4.0	MPV1-156	.335	.827	.394	.157	.016	
			8.5	21.0	10.0	4.0	0.4	
16-14A.W.G. 1.5-2.5mm <sup>2</sup>	.157 4.0	MPV1-156	.413	.906				
			10.5	23.0				
16-14A.W.G. 1.5-2.5mm <sup>2</sup>	.157 4.0	MPV2-156	.335	.827	.394	.177	.016	
			8.5	21.0	10.0	4.5	0.4	
16-14A.W.G. 1.5-2.5mm <sup>2</sup>	.197 5.0	MPV2-156	.413	.906				
			10.5	23.0				
12-10A.W.G. 4-65mm <sup>2</sup>	.197 5.0	MPV2-195	.335	.827				
			8.5	21.0				
12-10A.W.G. 4-65mm <sup>2</sup>	.197 5.0	MPV5-195	.335	.925	.512	.217	.016	
			8.5	23.5	13.0	5.5	0.4	




**NYLON-FULLY INSULATED BULLET DISCONNECTORS**  
**KST**  
 MAXIMUM ELECTRIC CURRENT:  
 22~16 A.W.G.:10 AMPERE  
 16~14 A.W.G.:15 AMPERE  
 MAXIMUM ELECTRICAL RATING:105°C 300 VOLTS MAX.  
 INSULATION MATERIAL: NYLON  
 TERMINAL MATERIAL: BRASS  
 INSULATION COLOR:  
 22-16 A.W.G.:RED  
 16-14 A.W.G.:BLUE  
 TERMINAL BARREL I.D.:  
 22-16 A.W.G.: C=1.7mm  
 16-14 A.W.G.: C=2.3mm



Wire range	A. W. G mm <sup>2</sup>	ITEM NO	W	F	L	B	D	T
22-16A.W.G. 0.5-1.5mm <sup>2</sup>	.157 4.0	MPFNVD1-156	.413	1.063	.394	.157	.016	
			10.5	27.0	10.0	4.0	0.4	
16-14A.W.G. 1.5-2.5mm <sup>2</sup>	.157 4.0	MPFNVD2-156	.413	1.063	.394	.177	.016	
			10.5	27.0	10.0	4.5	0.4	



**NYLON-FULLY INSULATED DOUBLE CRIMP RECEPTACLE DISCONNECTORS**  
**KST**  
 MAXIMUM ELECTRIC CURRENT:  
 22~16 A.W.G.:10 AMPERE  
 16~14 A.W.G.:15 AMPERE  
 MAXIMUM ELECTRICAL RATING:105°C 300 VOLTS MAX.  
 INSULATION MATERIAL: NYLON  
 TERMINAL MATERIAL: BRASS  
 INSULATION COLOR:  
 22-16 A.W.G.:RED  
 16-14 A.W.G.:BLUE  
 DOUBLE CRIMP: WITH COPPER SLEEVE ON BARREL  
 TERMINAL BARREL I.D.:  
 22-16 A.W.G.: C=1.7mm  
 16-14 A.W.G.: C=2.3mm



Wire range	A. W. G mm <sup>2</sup>	ITEM NO	W	F	L	B	D	T
22-16A.W.G. 0.5-1.5mm <sup>2</sup>	.153 3.9	FRFNVD1-156	.287	.992	.433	.157	.016	
			7.3	25.2	11.0	4.0	0.4	
16-14A.W.G. 1.5-2.5mm <sup>2</sup>	.153 3.9	FRFNVD2-156	.287	.992				
			7.3	25.2	4.33	.197	.016	
16-14A.W.G. 1.5-2.5mm <sup>2</sup>	.193 4.9	FRFNVD2-195	.276	1.063	11.0	5.0	0.4	
			7.0	27.0				


100Y 编号	厂商编号	制造厂商	说明	护套颜色	尺寸 L	护套 全/半角	耐温°C/Volt/A	压接线径 d	护套材质	公/母端子
7956	FRFNVD1-156	KST	105°C 母端子 16AWG	红色	27L*4.0W*4.0D	全角	105°C/300V	22-16AWG(0.5-1.5mm <sup>2</sup> )	Nylon	Female
4279	FRV1-156	KST	VINYL 护套子弹形母端子	RED	23L*4D*1.7Cmm	全角	75°C/300V	22-16AWG, 0.5-1.5mm <sup>2</sup>	VINYL	Female
4284	FRV2-156	KST	VINYL 护套子弹形母端子	BLUE	23.5L*4.5D*2.3Cmm	全角	75°C/300V	16-14AWG, 1.5-2.5mm <sup>2</sup>	VINYL	Female
4280	FRV5-195	KST	VINYL 护套子弹形母端子	YELLOW	24L*5.5D*3.4Cmm	全角	75°C/300V	10-12AWG, 4-6mm <sup>2</sup>	VINYL	Female
8764	MPFNVD1-156	KST	105°C 护套子弹	红色	27L*4.0W*4.0D	全角	105°C/300V	22-16AWG(0.5-1.5mm <sup>2</sup> )	Nylon	Male(公)
2464	MPV1-156	KST	VINYL 护套子弹形公端子	RED	21L*4D*1.7Cmm	半角	75°C/300V	22-16 AWG, 0.5-1.5mm <sup>2</sup>	VINYL	Male
5628	MPV2-156	KST	VINYL 护套子弹形公端子	BLUE	21L*4.5D*2.3Cmm	半角	75°C/300V	16-14AWG, 1.5-2.5mm <sup>2</sup>	VINYL	Male
11213	MPV5-195	KST	VINYL 护套子弹形公端子	Yellow	23.5L*5.5D*3.4Cmm	半角	75°C/300V	12-10AWG, 4-6mm <sup>2</sup>	VINYL	Male

刀型端子 (Vinyl, Nylon护套)


详细产品规格 - 请点击cn.100y.com.tw



**VINYL-FULLY INSULATED RECEPTACLE DISCONNECTORS**  
**KST**  
 MAXIMUM ELECTRIC CURRENT:  
 26-22 A.W.G.: 9 AMPERE  
 22~16 A.W.G.:19 AMPERE  
 16~14 A.W.G.:27 AMPERE  
 12~10 A.W.G.:48 AMPERE  
 MAXIMUM ELECTRICAL RATING:  
 75°C 600 VOLTS MAX.  
 INSULATION MATERIAL: VINYL  
 INSULATION COLOR:  
 26-22 A.W.G.:YELLOW  
 22-16 A.W.G.:RED  
 16-14 A.W.G.:BLUE  
 12-10 A.W.G.:YELLOW  
 TERMINAL MATERIAL: COPPER



**VINYL-INSULATED LIPPED BLADE TERMINALS**  
**KST**  
 MAXIMUM ELECTRIC CURRENT:  
 22~16 A.W.G.:19 AMPERE  
 16~14 A.W.G.:27 AMPERE  
 12~10 A.W.G.:48 AMPERE  
 MAXIMUM ELECTRICAL RATING:  
 75°C 600 VOLTS MAX.  
 INSULATION MATERIAL: VINYL  
 INSULATION COLOR:  
 22-16 A.W.G.:RED  
 16-14 A.W.G.:BLUE  
 12-10 A.W.G.:YELLOW  
 TERMINAL MATERIAL: COPPER



100Y 编号	厂商编号	说明	护套颜色	护套材质	耐温°C/Volt/A	尺寸 L*W*d1*D	压接线径
6492	DBV5-14	Vinyl 护套刀型端子	黄色	Vinyl	75°C/600V/48A	27*4.5*3.4*6.3	12-10AWG(4-6mm <sup>2</sup> )
11869	DBVS2-18	Vinyl 护套刀型端子	蓝色	Vinyl	75°C/600V/27A	27.8*2.0*2.3*4.5	16-14AWG(1.5-2.5mm <sup>2</sup> )
6473	LBV1-3	Vinyl 护套刀型端子	红色	Vinyl	75°C/600V/19A	27.2*3.0*1.7*4.0	22-16AWG(0.5-1.5mm <sup>2</sup> )
6477	LBV2-3	Vinyl 护套刀型端子	蓝色	Vinyl	75°C/600V/27A	27.2*3.0*2.3*4.5	16-14AWG(1.5-2.5mm <sup>2</sup> )
6475	LBV5-3	Vinyl 护套刀型端子	黄色	Vinyl	75°C/600V/48A	30.2*3.0*3.4*6.3	12-10AWG(4-6mm <sup>2</sup> )

