




叶片形公/母压线端子(Vinyl, Nylon护套)

详细产品规格 - 请点击cn.100y.com.tw



**VINYL-INSULATED DOUBLE CRIMP FEMALE DISCONNECTORS**  
 MAXIMUM ELECTRIC CURRENT: 26-22A.W.G.: 3 AMPERE  
 INSULATION MATERIAL: VINYL  
 DOUBLE CRIMP: WITH COPPER SLEEVE ON BARREL  
 TERMINAL BARREL I.D.: 26-22 A.W.G.: C=1.0mm


MAXIMUM ELECTRICAL RATING: 75°C 300 VOLTS MAX  
 INSULATION COLOR: 26-22 A.W.G.: YELLOW



Wire range A. W. G mm <sup>2</sup>	ITEM NO	NEMA TAB	DIMENSION <sup>Inch</sup> / <sub>mm</sub>						FIG
			W	F	L	B	D	T	
26-22A.W.G. 0.2-0.5mm <sup>2</sup>	FDD0.5-110(5)	0.20x.110 (0.5x2.8)	.126	.252	.630	.031	.110	.010	1
	FDD0.5-110(8)	.32x.110 (0.8x2.8)	3.2	6.4	16.0	8.0	2.8	0.25	2




**VINYL-INSULATED DOUBLE CRIMP FEMALE DISCONNECTORS**  
 MAXIMUM ELECTRIC CURRENT: 26-22 A.W.G.: 10 AMPERE  
 MAXIMUM ELECTRICAL RATING: 75°C 300 VOLTS MAX  
 INSULATION MATERIAL: VINYL  
 INSULATION COLOR: 22-16 A.W.G.: Red  
 DOUBLE CRIMP: WITH COPPER SLEEVE ON BARREL  
 TERMINAL MATERIAL: BRASS  
 TERMINAL BARREL I.D.: 22-16 A.W.G.: C=1.7mm



Wire range A. W. G mm <sup>2</sup>	ITEM NO	NEMA TAB	DIMENSION <sup>Inch</sup> / <sub>mm</sub>						FIG
			W	F	L	B	D	T	
26-22A.W.G. 0.2-0.5mm <sup>2</sup>	FDD1-110(5)	0.20x.110 (0.5x2.8)	.126	.256	.728	.413	.150	.012	1
	FDD1-110(8)	.32x.110 (0.8x2.8)	3.2	6.5	19.0	10.5	3.8	0.3	
22-16A.W.G. 0.5-1.5mm <sup>2</sup>	FDD1-187(5)	0.20x.187 (0.5x4.75)	.197	.252	.764			.016	2
	FDD1-187(8)	.32x.187 (0.8x4.75)	5.0	6.4	19.4			0.4	
22-16A.W.G. 0.5-1.5mm <sup>2</sup>	FDD1-205	0.20x.205 (0.5x5.2)	.224	.260	.760			.014	1
	FDD1-250	0.32x.250 (0.8x6.35)	.260	.287	.819			.016	
	FDD1-312	0.32x.312 (0.8x8.0)	.323	.394	.965			.016	
	FDD1-312	0.32x.312 (0.8x8.0)	8.2	10.0	24.5			0.4	




**NYLON-FULLY INSULATED DOUBLE CRIMP FEMALE & DISCONNECTORS**  
 MAXIMUM ELECTRIC CURRENT: 22-16 A.W.G.: 10 AMPERE  
 16-14 A.W.G.: 15 AMPERE  
 12-10 A.W.G.: 24 AMPERE  
 MAXIMUM ELECTRICAL RATING: 105°C 300 VOLTS MAX.  
 INSULATION MATERIAL: NYLON  
 TERMINAL MATERIAL: BRASS  
 INSULATION COLOR:  
 22-16 A.W.G.: RED  
 16-14 A.W.G.: BLUE  
 12-10 A.W.G.: YELLOW  
 DOUBLE CRIMP: WITH COPPER SLEEVE ON BARREL  
 TERMINAL BARREL I.D.: 22-16 A.W.G.: C=1.7mm  
 16-14 A.W.G.: C=2.3mm 12-10 A.W.G.: C=3.4mm



Wire range A. W. G mm <sup>2</sup>	ITEM NO	NEMA TAB	DIMENSION <sup>Inch</sup> / <sub>mm</sub>						FIG
			W	F	L	B	D	T	
22-16A.W.G. 0.5-1.5mm <sup>2</sup>	DFDNYD1-110(5)	0.21x.110 (0.5x2.8)	.126	.252	.768			.012	1
	DFDNYD1-110(8)	.32x.110 (0.8x2.8)	3.2	6.4	19.5			0.3	
22-16A.W.G. 0.5-1.5mm <sup>2</sup>	DFDNYD1-187(5)	0.20x.187 (0.5x4.75)	.197	.256	.795	.413	.157	.016	2
	DFDNYD1-187(8)	.32x.187 (0.8x4.75)	5.0	6.5	20.2	10.5	4.0	0.4	
16-14A.W.G. 1.5-2.5mm <sup>2</sup>	DFDNYD1-250	0.32x.250 (0.8x6.35)	.260	.303	.846			.016	1
	DFDNYD2-187(5)	0.20x.187 (0.5x4.75)	.197	.256	.795	.433	.197	.016	
16-14A.W.G. 1.5-2.5mm <sup>2</sup>	DFDNYD2-187(8)	.32x.187 (0.8x4.75)	5.0	6.5	20.2	11.0	5.0	0.4	2
	DFDNYD2-250	0.32x.250 (0.8x6.35)	.260	.287	.846			.016	
12-10A.W.G. 4-6.5mm <sup>2</sup>	DFDNYD5-250	0.32x.250 (0.8x6.35)	.260	.287	.846	.512	.256	.016	2
	DFDNYD5-250	0.32x.250 (0.8x6.35)	6.6	7.3	24.2	13.0	6.5	0.4	




**NYLON-FULLY INSULATED FEMALE & MALE DISCONNECTORS**  
 MAXIMUM ELECTRIC CURRENT: 22-16 A.W.G.: 10 AMPERE  
 16-14 A.W.G.: 15 AMPERE  
 12-10 A.W.G.: 24 AMPERE  
 MAXIMUM ELECTRICAL RATING: 105°C 300 VOLTS MAX.  
 INSULATION MATERIAL: NYLON  
 INSULATION COLOR:  
 22-16 A.W.G.: RED  
 16-14 A.W.G.: BLUE  
 12-10 A.W.G.: YELLOW  
 TERMINAL MATERIAL: BRASS



Wire range A. W. G mm <sup>2</sup>	ITEM NO	NEMA TAB	DIMENSION <sup>Inch</sup> / <sub>mm</sub>						FIG
			W	F	L	B	D	T	
22-16A.W.G. 0.5-1.5mm <sup>2</sup>	DFDNYD1-250	0.32x.250 (0.8x6.35)	.260	.287	.866	.413	.157	.016	1
	MDFN1-250	0.32x.250 (0.8x6.35)	6.6	7.3	22.0	10.5	4.0	0.4	
16-14A.W.G. 1.5-2.5mm <sup>2</sup>	DFDNYD2-250	0.32x.250 (0.8x6.35)	.260	.287	.866	.433	.177	.016	1
	MDFN2-250	0.32x.250 (0.8x6.35)	.250	.303	.945	11.0	4.5	0.4	
12-10A.W.G. 4-6.5mm <sup>2</sup>	DFDNYD5-250	0.32x.250 (0.8x6.35)	.260	.287	.846	.512	.248	.016	1
	MDFN5-250	0.32x.250 (0.8x6.35)	6.6	7.3	24.0	13.0	6.3	0.4	



**NYLON-FULLY INSULATED FEMALE & MALE DISCONNECTORS**  
 MAXIMUM ELECTRIC CURRENT: 22-16 A.W.G.: 10 AMPERE  
 16-14 A.W.G.: 15 AMPERE  
 12-10 A.W.G.: 24 AMPERE  
 MAXIMUM ELECTRICAL RATING: 105°C 300 VOLTS MAX.  
 INSULATION MATERIAL: NYLON  
 INSULATION COLOR:  
 22-16 A.W.G.: RED  
 16-14 A.W.G.: BLUE  
 12-10 A.W.G.: YELLOW  
 TERMINAL MATERIAL: BRASS  
 TERMINAL BARREL I.D. 22-16 A.W.G.: C=1.7mm  
 16-14 A.W.G.: C=2.3mm 12-10 A.W.G.: C=3.4mm



Wire range A. W. G mm <sup>2</sup>	ITEM NO	NEMA TAB	DIMENSION <sup>Inch</sup> / <sub>mm</sub>						FIG
			W	F	L	B	D	T	
22-16A.W.G. 0.5-1.5mm <sup>2</sup>	DFDNYD1-250	0.32x.250 (0.8x6.35)	.260	.287	.866	.413	.157	.016	1
	MDFN1-250	0.32x.250 (0.8x6.35)	6.6	7.3	22.0	10.5	4.0	0.4	
16-14A.W.G. 1.5-2.5mm <sup>2</sup>	DFDNYD2-250	0.32x.250 (0.8x6.35)	.260	.287	.866	.433	.177	.016	1
	MDFN2-250	0.32x.250 (0.8x6.35)	.250	.303	.945	11.0	4.5	0.4	
12-10A.W.G. 4-6.5mm <sup>2</sup>	DFDNYD5-250	0.32x.250 (0.8x6.35)	.260	.287	.846	.512	.248	.016	1
	MDFN5-250	0.32x.250 (0.8x6.35)	6.6	7.3	24.0	13.0	6.3	0.4	

100Y 编号	厂商编号	制造厂商	护套颜色	尺寸 L*W*C*D	压接线径	护套全/半角	耐温°C/Volt/A	护套材质	公/母端子	说明
6465	FDD0.5-110(5)	KST	黄色	16*3.2*C1.0mm	26-22AWG(0.2-0.5mm <sup>2</sup> )	半	75°C/300V	Vinyl	Female	75°C叶片母端子
6468	FDD1-250G	KST	红色	20.8*6.6*1.7mm	22-16AWG 0.5-1.5mm <sup>2</sup>	半角	75°C	Vinyl	镀金母端子	镀金叶片形母压线端子
8294	DFDNYD1-250-CLEAR	KST	红色	22*6.6*1.7mm	22-16AWG(0.5-1.5mm <sup>2</sup> )	全角	105°C/300V	Nylon	Female	105°C母端子 16AWG
5620	DFDNY2-250	KST	Blue	22*6.6*2.3mm	16-14AWG(1.5-2.5mm <sup>2</sup> )	全角	105°C	Nylon-Fully	Female	105°C叶片形母压线端子
6497	DFDNYD1-250	KST	红色	22.5*6.6*1.7mm	22-16AWG(0.5-1.5mm <sup>2</sup> )	全	105°C/300V	Nylon	Female	105°C母端子 (100个/包)
6449	DFDNY2-250	KST	蓝色	23*6.6*2.3mm	16-14AWG(1.5-2.5mm <sup>2</sup> )	全	105°C/300V	Nylon	Female	105°C叶片端子母 14AWG
6499	DFDNY5-250	KST	黄色	23*6.6*3.4mm	12-10AWG(4-6mm <sup>2</sup> )	全	105°C/300V/24A	Nylon	Female	105°C母端子 10AWG 24A (100个/包)
12906	DFDNYD1-110(8)	KST	红色	19.5*3.2*1.7	22-16AWG(0.5-1.5mm <sup>2</sup> )	全	105°C/300V/10A	Nylon	female	105°C母端子 16AWG 10A
27122	DFDNYD1-187(8)	KST	红色	20.2*5*1.7*4	22-16AWG(0.5-1.5mm <sup>2</sup> )	全	105°C/300V/10A	Nylon	female	105°C母端子 16AWG 10A
10752	MDFN1-250-CLEAR	KST	浅红色	23mm	22-16AWG(0.5-1.25mm <sup>2</sup> )	全角	105°C	Nylon-Fully	Male	浅红色耐高温叶片形公压线端子(100个/包)
10750	MDFN2-250-CLEAR	KST	浅蓝色	24*6.35	16-14AWG(1.5-2.5mm <sup>2</sup> )	全角	105°C/300V	Nylon	Male	耐高温端子/线径:2mm (100个/包)
6439	MDFNYD1-250	KST	红色	0.250*0.032*6.35*0.8	22-16AWG(0.5-1.5mm <sup>2</sup> )	全	105°C/300V	Nylon	Male	全护套叶片端子公插 (100个/包)
6453	MDFNY2-250	KST	蓝色	24.5*6.35	16-14AWG(1.5-2.5mm <sup>2</sup> )	全	105°C/300V	Nylon	Male	耐高温护套叶片端子公
6445	MDFNY5-250	KST	黄色	24.5*6.35	12-10AWG(4-6mm <sup>2</sup> )	全	105°C/300V	Nylon	Male	耐高温护套叶片端子公

