




叶片形公/母压线端子(Vinyl, Nylon护套)

详细产品规格 - 请点击cn.100y.com.tw




VINYL-FULLY INSULATED FEMALE DISCONNECTORS
 MAXIMUM ELECTRIC CURRENT:
 22~16 A.W.G.:10 AMPERE
 16~14 A.W.G.:15 AMPERE
 12~10 A.W.G.:24 AMPERE
 MAXIMUM ELECTRICAL RATING:
 75°C 300 VOLTS MAX.
 INSULATION MATERIAL: VINYL
 TERMINAL MATERIAL: BRASS
 INSULATION COLOR:
 22-16 A.W.G.: RED
 16-14 A.W.G.: BLUE
 12-10 A.W.G.: YELLOW
 DOUBLE CRIMP: WITH COPPER SLEEVE ON BARREL
 TERMINAL BARRED I.D.: 22-16 A.W.G.: C=1.7mm
 16-14 A.W.G.: C=2.3mm 12-10 A.W.G.: C=3.4mm



Wire range A.W.G mm ²	ITEM NO	NEMA TAB	W	DIMENSION ^{Inch}			B	D	T	FIG
				F	L					
22-16A.W.G. 0.5-1.5mm ²	DFDNYD1-187(5)	0.20x.187 (0.5x4.75)	.197	.252	.760	.413	.157	.016	1	
	DFDNYD1-187(8)	0.32x.187 (0.8x4.75)	5.0	6.4	19.3	10.5	4.0	0.4		
	DFDNYD1-250	0.32x.250 (0.8x6.35)	.260	.287	.866			.1547		2
16-14A.W.G. 1.5-2.5mm ²	DFDNYD2-187(5)	0.20x.187 (0.5x4.75)	.197	.252	.7606	.433	.177	.016	1	
	DFDNYD2-187(8)	0.32x.187 (0.8x4.75)	5.0	6.4	19.3	10.5	4.5	0.4		
12-10A.W.G. 4-65mm ²	DFDNYD2-250	0.32x.250 (0.8x6.35)	.260	.287	.866					
	DFDNYD5-250	0.32x.250 (0.8x6.35)	.260	.287	.957	.492	.217	.016	1	




VINYL-INSULATED MALE DISCONNECTORS
 MAXIMUM ELECTRIC CURRENT:
 22~16 A.W.G.:10 AMPERE
 16~14 A.W.G.:15 AMPERE
 12~10 A.W.G.:24 AMPERE
 MAXIMUM ELECTRICAL RATING:
 75°C 300 VOLTS MAX.
 INSULATION MATERIAL: VINYL
 TERMINAL MATERIAL: BRASS
 INSULATION COLOR:
 22-16 A.W.G.: RED
 16-14 A.W.G.: BLUE
 12-10 A.W.G.: YELLOW
 TERMINAL BARREL I.D.:
 22-16 A.W.G.:C=1.7mm
 16-14 A.W.G.:C=2.3mm 12-10 A.W.G.:C=3.4mm



Wire range A.W.G mm ²	ITEM NO	NEMA TAB	W	DIMENSION ^{Inch}			B	D	T
				F	L				
22-16A.W.G. 0.5-1.5mm ²	MDV1-110(5)	0.20x.110 (0.5x2.8)	.110	.256	.728			.020	0.5
	MDV1-110(8)	0.32x.110 (0.8x2.8)	2.8	6.5	18.5			.016	0.4
	MDV1-187(5)	0.20x.187 (0.5x4.75)	.189	.256	.748	.394	.157	.020	0.5
16-14A.W.G. 1.5-2.5mm ²	MDV2-187(5)	0.20x.187 (0.5x4.75)	.189	.256	.748	.394	.177	.020	0.5
	MDV2-187(8)	0.32x.187 (0.8x4.75)	4.8	6.5	19.0	10.0	4.5	.016	0.4
12-10A.W.G. 4-65mm ²	MDV2-250	0.32x.250 (0.8x6.35)	.250	.303	.827				
	MDV5-250	0.32x.250 (0.8x6.35)	.250	.303	.945	.512	.217	.016	0.4



VINYL-INSULATED FEMALE DISCONNECTORS
 MAXIMUM ELECTRIC CURRENT:
 22~16 A.W.G.:10 AMPERE
 16~14 A.W.G.:15 AMPERE
 12~10 A.W.G.:24 AMPERE
 MAXIMUM ELECTRICAL RATING:
 75°C 300 VOLTS MAX.
 INSULATION MATERIAL: VINYL
 TERMINAL MATERIAL: BRASS
 INSULATION COLOR:
 22-16 A.W.G.: RED
 16-14 A.W.G.: BLUE
 12-10 A.W.G.: YELLOW
 TERMINAL BARREL I.D.:22-16 A.W.G.:C=1.7mm
 16-14 A.W.G.:C=2.3mm 12-10 A.W.G.:C=3.4mm



Wire range A.W.G mm ²	ITEM NO	NEMA TAB	W	DIMENSION ^{Inch}			B	D	T
				F	L				
22-16A.W.G. 0.5-1.5mm ²	FDV1-110(5)	0.20x.110 (0.5x2.8)	.126	.256	.732			.012	0.3
	FDV1-110(8)	0.32x.110 (0.8x2.8)	3.2	6.5	18.6				
	FDV1-187(5)	0.20x.187 (0.5x4.75)	.197	.252	.748	.394	.157	.016	0.4
16-14A.W.G. 1.5-2.5mm ²	FDV2-110(5)	0.20x.110 (0.5x2.8)	.126	.256	.732			.012	0.3
	FDV2-110(8)	0.32x.110 (0.8x2.8)	3.2	6.5	18.6				
12-10A.W.G. 4-65mm ²	FDV2-187(5)	0.20x.187 (0.5x4.75)	.197	.252	.748	.394	.177	.016	0.4
	FDV2-187(8)	0.32x.187 (0.8x4.75)	5.0	6.4	19.0				
12-10A.W.G. 4-65mm ²	FDV5-110(5)	0.20x.110 (0.5x2.8)	.126	.256	.866			.016	0.4
	FDV5-110(8)	0.32x.110 (0.8x2.8)	3.2	6.5	22.0				



Wire range A.W.G mm ²	ITEM NO	NEMA TAB	DIMENSION ^{Inch}	
			W	
16-14A.W.G. 1.5-2.5mm ²	PBDV2-250	0.031 (0.8)	0.260 (6.60)	

100Y 编号	厂商编号	制造厂商	护套颜色	尺寸 L*W*C*D	压接线径	护套 全/半角	耐温°C/Volt/A	护套材质	公/母端子	说明
7828	DFDV1-250	KST	RED	22*6.6*1.7mm	22-16 AWG 0.5-1.5mm ²	全角	75°C/300V	Vinyl-Fully	Female	护套叶片形母压线端子
7827	DFDV2-250	KST	Blue	22*6.6*2.3mm	16-14AWG(1.5-2.5mm ²)	全角	75°C/300V	Vinyl-Fully	Female	护套叶片形母压线端子
9105	DFDV5-250	KST	黄色	24.3*6.6*3.4mm	12-10AWG(4-6mm ²)	全	75°C/300V/24A	Vinyl	Female	75°C 母端子 10AWG 24A
8290	FDV1-110(5)	KST	Red	18.6mm	22-16AWG(0.5-1.5mm ²)	半角	75°C	Vinyl	Female	叶片母压线端子 (100 个/包)
6536	FDV1-187(8)	KST	Red	19mm	22-16AWG(0.5-1.5mm ²)	半角	75°C	Vinyl	Female	护套叶片形母压线端子
40553	FDV1-205	KST	BLUE	24mm	22-16AWG(0.5-1.5mm ²)	半角	75°C	Vinyl	Female	护套叶片形母压线端子
7963	FDV1-250	KST	Red	20.5mm	22-16AWG(0.5-1.5mm ²)	半角	75°C	Vinyl	Female	护套叶片形母压线端子
8292	FDV2-110(5)	KST	BLUE	18.6mm	16-14AWG(1.5-2.5mm ²)	半角	75°C	Vinyl	Female	护套叶片形母压线端子
40552	FDV2-187(5)	KST	BLUE	24mm	16-14AWG(1.5-2.5mm ²)	半角	75°C	Vinyl	Female	护套叶片形母压线端子 (1000 个/包)
4277	FDV2-187(8)	KST	BLUE	19mm	16-14AWG(1.5-2.5mm ²)	半角	75°C	Vinyl	Female	护套叶片形母压线端子
4282	FDV2-250	KST	BLUE	20.5mm	16-14AWG(1.5-2.5mm ²)	半角	75°C	Vinyl	Female	护套叶片形母压线端子 (100 个/包)
22087	FDV2-312	KST	BLUE	24mm	16-14AWG(1.5-2.5mm ²)	半角	75°C	Vinyl	Female	护套叶片形母压线端子 (100 个/包)
4273	FDV5-250	KST	YELLOW	23.5mm	12-10AWG(4-6mm ²)	半角	75°C	Vinyl	Female	护套叶片形母压线端子 (100 个/包)
12967	MDV1-110(5)	KST	RED	18.5*2.8mm	22-16AWG(0.5-1.5mm ²)	半角	75°C	Vinyl	Male	叶片形公压线端子
12963	MDV1-187(5)	KST	RED	19*4.8mm	22-16AWG(0.5-1.5mm ²)	半角	75°C	Vinyl	Male	叶片形公压线端子
8296	MDV1-250	KST	RED	21*6.35mm	22-16AWG(0.5-1.5mm ²)	半角	75°C	Vinyl	Male	叶片形公压线端子
12965	MDV2-187(5)	KST	BLUE	19*4.8	16-14AWG(1.5-2.5mm ²)	半角	75°C	Vinyl	Male	叶片形公压线端子
11183	MDV2-250	KST	蓝色	21*6.35mm	16-14AWG(1.5-2.5mm ²)	半角	75°C	Vinyl	Male	叶片形公压线端子
10741	MDV5-250	KST	黄色	24*6.35mm	12-10AWG(4-6mm ²)	半角	75°C	Vinyl	Male	叶片形公压线端子
16617	PBDV1-250		红色	22*6.6*1.7*4mm	22-19AWG(0.5-1.5mm ²)	半角	75°C/300V/10A	Vinyl	Male/Female	叶片形公母压线端子
16618	PBDV2-250		蓝色	22*6.6*2.3*4.5mm	16-14AWG(1.5-2.5mm ²)	半角	75°C/300V/15A	Vinyl	Male/Female	叶片形公母压线端子

