



## 叶片形公/母压线端子(Vinyl, Nylon护套)

## 详细产品规格 - 请点击cn.100y.com.tw

**NYLON-INSULATED FLAG FEMALE DISCONNECTORS**  
 MAXIMUM ELECTRIC CURRENT:  
 22-18 A.W.G.:10 AMPERE  
 16-14 A.W.G.:15 AMPERE  
 MAXIMUM ELECTRICAL RATING:  
 105°C 300 VOLTS MAX.  
 INSULATION MATERIAL: NYLON  
 INSULATION COLOR:  
 22-18 A.W.G.:RED  
 16-14 A.W.G.:BLUE  
 TERMINAL MATERIAL: BRASS

Wire range A. W. G mm <sup>2</sup>	ITEM NO	NEMATAB	W	DIMENSION Inch mm			
				F	L	d1	T
22-18A.W.G. 0.5-1.5mm <sup>2</sup>	FLDNY1-250	0.32x.250 (0.8x6.35)	.260 6.6	.299 7.6	.630 16.0	.067 1.7	.016 0.4
16-14A.W.G. 1.5-2.5mm <sup>2</sup>	FLDNY2-250	0.32x.250 (0.8x6.35)	.260 6.6	.299 7.6	.630 16.0	.091 2.3	.016 0.4

**NYLON-FULLY INSULATED DOUBLE CRIMP MALE DISCONNECTORS**  
 MAXIMUM ELECTRIC CURRENT:  
 22-16 A.W.G.:10 AMPERE  
 16-14 A.W.G.:15 AMPERE  
 MAXIMUM ELECTRICAL RATING:  
 105°C 300 VOLTS MAX.  
 INSULATION MATERIAL: NYLON  
 INSULATION COLOR:  
 22-16 A.W.G.:RED  
 16-14 A.W.G.:BLUE  
 TERMINAL MATERIAL: BRASS

Wire range A. W. G mm <sup>2</sup>	ITEM NO	NEMATAB	W	DIMENSION Inch mm					
				F	L	B	D	T	
22-16A.W.G. 0.5-1.5mm <sup>2</sup>	MDFNYD1-250	0.32x.250 (0.8x6.35)	.250 6.35	.303 7.7	.976 24.0	.433 11.0	.157 4.0	.016 0.4	
16-14A.W.G. 1.5-2.5mm <sup>2</sup>	MDFNYD2-250	0.32x.250 (0.8x6.35)	.250 6.35	.303 7.7	.976 24.0	.433 11.0	.197 5.0	.016 0.4	

100Y 编号	厂商编号	制造厂商	护套颜色	尺寸 L*W*C*D	压接线径	护套 全/半角	耐温°C/Volt/A	护套材质	公/母端子	说明
9107	FLDNY1-250	KST	红色	16*6.6*	22-18AWG(0.5-1.5mm2)	全	105°C/300V/10A	Nylon	Female	105°C母端子 18AWG 10A
12278	FLDNY2-250	KST	蓝色	16*6.6	16-14AWG(1.5-2.5mm2)	全	105°C/300V/15A	Nylon	Female	耐高温母端子 (100 个/包)
12986	MDFNYD1-250	KST	红色	24*6.35mm	22-16AWG(0.5-1.5mm2)	全	105°C/300V	Nylon	Male	耐高温护套插型公
20267	MDFNYD2-250	KST	蓝色	24*6.35mm	16-14AWG(1.5-2.5mm2)	全	105°C/300V	Nylon	Male	耐高温护套插型公

## 前凸 'Y' 型压线端子(Vinyl, Nylon护套)

**VINYL-INSULATED FLANGE SPADE TERMINALS**  
 MAXIMUM ELECTRIC CURRENT:  
 22-16 A.W.G.:19 AMPERE  
 16-14 A.W.G.:27 AMPERE  
 12-10 A.W.G.:48 AMPERE  
 MAXIMUM ELECTRICAL RATING:  
 75°C 600 VOLTS MAX.  
 INSULATION MATERIAL: NYLON  
 INSULATION COLOR:  
 22-16 A.W.G.:RED  
 16-14 A.W.G.:BLUE  
 12-10 A.W.G.:YELLOW  
 TERMINAL MATERIAL: COPPER

Wire range A. W. G mm <sup>2</sup>	ITEM NO	BRAZED SEAM	BUTTED SEAM	STUD SIZE D1	DIMENSION Inch mm							
					W	F	L	E	D	d1	A	T
22-16A.W.G. 0.5-1.5mm <sup>2</sup>	FSVB1-4	FSV1-4	#8	.169 4.3	.295 7.5	.201 5.1	.748 19.0	.394 10.0	.157 4.0	.067 1.7	.059 1.5	.030 0.75
	FSVB1-5	FSV1-5	#10	.209 5.3	.295 7.5	.201 5.1	.748 19.0	.394 10.0	.157 4.0	.067 1.7	.059 1.5	.030 0.75
	FSVB2-4	FSV2-4	#8	.169 4.3	.295 7.5	.205 5.2	.768 19.5	.394 10.0	.177 4.5	.091 2.3	.059 1.5	.031 0.8

100Y 编号	厂商编号	说明	护套颜色	尺寸 L*W*d2	压接线径	护套 全/半形	耐温°C/Volt/A	护套材质
4913	FSV1-4	护套'Y'形前凸压线端子	RED	19*7.5*#8	22-16AWG(0.5-1.5mm2)	半形	75°C	VINYL
4912	FSV1-5	护套'Y'形前凸压线端子	RED	19*7.5*#10	22-16AWG(0.5-1.5mm2)	半形	75°C	VINYL
2963	FSV1-5-门市包装	护套'Y'形前凸压线端子	RED	19*7.5*#10	22-16AWG(0.5-1.5mm2)	半形	75°C	VINYL
4914	FSV2-4	护套'Y'形前凸压线端子	BLUE	19.5*7.5*#8	16-14AWG(1.5-2.5mm2)	半形	75°C	VINYL

## 'Y' 型压线端子(Vinyl, Nylon护套)

## 详细产品规格 - 请点击cn.100y.com.tw

**VINYL-INSULATED SPADE TERMINALS**  
 MAXIMUM ELECTRIC CURRENT:  
 22-16 A.W.G.:19 AMPERE  
 16-14 A.W.G.:27 AMPERE  
 12-10 A.W.G.:48 AMPERE  
 MAXIMUM ELECTRICAL RATING:  
 75°C 600 VOLTS MAX.  
 INSULATION MATERIAL: NYLON  
 INSULATION COLOR:  
 22-16 A.W.G.:RED  
 16-14 A.W.G.:BLUE  
 14-12 A.W.G.:BLACK  
 12-10 A.W.G.:YELLOW  
 TERMINAL MATERIAL: COPPER

Wire range A. W. G mm <sup>2</sup>	ITEM NO	BRAZED SEAM	BUTTED SEAM	STUD SIZE D1	DIMENSION Inch mm						
					W	F	L	E	D	d1	T
22-16A.W.G. 0.5-1.5mm <sup>2</sup>	SVBS1-3.7	SVS1-3.7	#6	.146 3.7	.323 8.2	.256 6.5	.827 21.0	.394 10.0	.157 4.0	.067 1.7	.030 0.75
	SVBM1-4	SVM1-4	#8	.169 4.3	.283 7.2	.256 6.5	.827 21.0	.394 10.0	.157 4.0	.067 1.7	.030 0.75
	SVBL1-5	SVL1-5	#10	.209 5.3	.374 9.5	.224 5.7	.827 21.0	.394 10.0	.177 4.5	.091 2.3	.031 0.8
16-14A.W.G. 1.5-2.5mm <sup>2</sup>	SVBS2-3.7	SVS2-3.7	#6	.146 3.7	.323 8.2	.256 6.5	.827 21.0	.394 10.0	.157 4.0	.067 1.7	.030 0.75
	SVBM2-4	SVM2-4	#8	.169 4.3	.283 7.2	.256 6.5	.827 21.0	.394 10.0	.177 4.5	.091 2.3	.031 0.8
	SVBL2-5	SVL2-5	#10	.209 5.3	.366 9.3	.276 7.0	.827 21.0	.394 10.0	.134 3.4	.039 1.0	
12-10A.W.G. 4-6mm <sup>2</sup>	SVB5-5	SV5-5	#10	.209 5.3	.276 7.0	.472 12.0	1.004 25.5	.512 13.0	.248 6.3	.134 3.4	.039 1.0
	SVBL5-6	SVL5-6	1/4"	.252 6.4	.472 12.0	.315	1.240	13.0	6.3	3.4	1.0

100Y 编号	厂商编号	说明	护套颜色	尺寸 L*W*d2	压接线径	护套 全/半角	耐温°C/Volt/A	护套材质
4910	SV5-5	护套'Y'形压线端子	YELLOW	25.5*9*#10	12-10AWG(4-6mm2)	半角	75°C	VINYL
4908	SVL1-5	护套'Y'形压线端子	RED	21*9.5*#10	22-16AWG(0.5-1.5mm2)	半角	75°C	VINYL
4909	SVL2-5	护套'Y'形压线端子	BLUE	21*9.3*#10	16-14AWG(1.5-2.5mm2)	半角	75°C	VINYL
4911	SVL5-6	护套'Y'形压线端子	YELLOW	31.5*12*1/4	12-10AWG(4-6mm2)	半角	75°C	VINYL
4907	SVM1-4	护套'Y'形压线端子	RED	21*7.2*#8	22-16AWG(0.5-1.5mm2)	半角	75°C	VINYL
4260	SVM2-4	护套'Y'形压线端子	BLUE	21*7.2*#8	16-14AWG(1.5-2.5mm2)	半角	75°C	VINYL
17751	SVM2-4-YELLOW	护套'Y'形压线端子	YELLOW	21*7.2*#8	16-14AWG(1.5-2.5mm2)	半角	75°C	VINYL
5626	SVS1-3.7	护套'Y'形压线端子	RED	21*5.7*#6	22-16AWG(0.5-1.5mm2)	半角	75°C	VINYL
4286	SVS2-3.7	护套'Y'形压线端子	BLUE	21*5.7*#6	16-14AWG(1.5-2.5mm2)	半角	75°C	VINYL

※每月有上百种新增产品, 若您在目录上找不以您需要的元件, 请来电或上网查询。  
 ※您也可请我们代订商品, 欢迎您的来电。

