




'R' 圆型压线端子(Vinyl, Nylon护套)


详细产品规格 - 请点击cn.100y.com.tw



VINYL-INSULATED RING TERMINALS
 MAXIMUM ELECTRIC CURRENT:
 12-10 A.W.G.:48 AMPERE
 8 A.W.G.: 62 AMPERE
 6 A.W.G.: 88 AMPERE
 2 A.W.G.: 160 AMPERE
 MAXIMUM ELECTRICAL RATING:
 105°C 600 VOLTS MAX.
 INSULATION MATERIAL: NYLON
 INSULATION COLOR:
 12-10 A.W.G.:YELLOW
 8 A.W.G.:RED
 6 A.W.G.:BLUE
 2 A.W.G.:RED
 TERMINAL MATERIAL: COPPER



Wire range A. W. G mm ²	ITEM NO BRAZED SEAM	NO BUTTED SEAM	STUD SIZE D2	DIMENSION Inch mm						
				W	F	L	E	D	d1	T
8A. W. G 8mm ²	RNYBS8-6		1/4 6.4	.472 12.0	.366 9.3	1.232 31.3	.630 16.0	.315 8.0	.177 4.5	.047 1.2



RVS3-5

ITEM NO	BOLT NUMBER	D2	B(mm)	DIMENSION			
				L(mm)	F(mm)	H(mm)	D(mm)
RV3. 5-4	#8	4.3mm	8.0	24.5	7.7		
RVS3-5	#10	5.3mm	8.0	24.5	7.7	12.5	6.2
RVL3. 5-5	#10	5.3mm	12.0	27.9	7.7		
RV3. 5-6	1/4	6.5mm	12.0	27.9	7.7		




DRNY4-0.5

Wire range A. W. G mm ²	ITEM NO BRAZED SEAM	NO BUTTED SEAM	STUD SIZE D2	DIMENSION Inch mm		Q' TY BOX
				D3		
26-22A. W. G 0.2-0.5mm ²	DRNYB4-0.5	DRNY4-0.5	#8 4.3	.169 4.3	.256 6.50	1000



VINYL-INSULATED RING TERMINALS
 MAXIMUM ELECTRIC CURRENT:
 22-16 A.W.G.:19 AMPERE
 16-14 A.W.G.:27 AMPERE
 14-12 A.W.G.:37 AMPERE
 12-10 A.W.G.:48 AMPERE
 MAXIMUM ELECTRICAL RATING:
 75°C 600 VOLTS MAX.
 INSULATION MATERIAL: VINYL
 INSULATION COLOR:
 22-16 A.W.G.:RED
 16-14 A.W.G.:BLUE
 14-12 A.W.G.:BLACK
 12-10 A.W.G.:48 YELLOW
 TERMINAL MATERIAL: COPPER



Wire range A. W. G mm ²	ITEM NO BRAZED SEAM	NO BUTTED SEAM	STUD SIZE d2	DIMENSION inch mm						
				W	F	L	E	D	d1	T
	RVBS1-3.7	RV1-3.2	#6	.146 3.7	.216 5.5	.197 5.0	.689 17.5			
	RVBL1-4	RVL1-4	#8	.169 4.3	.315 8.0	.276 7.0	.819 20.8	.394 10.0	.157 4.0	.030 0.75
22-16 A. W. G. 0.5-1.5mm ²	RVB1-5	RV1-5	#10	.209 5.3	.475 12.0	.433 11.0	1.055 26.8			
	RVB1-6	RV1-6	1/4	.252 6.4	.475 11.6	.433 11.0	1.055 26.8			
	RVBS2-3.7	RVS2-3.7	#6	.146 3.7	.260 6.6	.189 4.8	.701 17.8			
	RVBL2-4	RVL2-4	#8	.169 4.3	.335 8.5	.307 7.8	.858 21.8	.394 10.0	.177 4.5	.091 2.3
16-14 A. W. G. 1.5-2.5mm ²	RVBS2-5	RVS2-5	#10	.209 5.3	.335 8.5	.307 7.8	.858 21.8			
	RVB2-6	RV2-6	1/4	.252 6.4	.472 12.0	.433 11.0	1.055 26.8			
14-12 A. W. G. 2.5-4mm ²	RVB3-4	RV3-4	#8	.169 4.3	.315 8.0	.303 7.7	.984 25.0	.512 13.0	.248 6.3	.188 3.0
	RVB5-3.7	RV5-3.7	#6	.146 3.7	.283 7.2	.240 6.1	.894 22.7			
	RVBL5-4	RVL5-4	#8	.169 4.3	.374 9.1	.358 9.1	1.047 26.6	.512 13.0	.248 6.3	.134 3.4
12-10 A. W. G. 4-6mm ²	RVBL5-5	RV5-5	#10	.209 5.3	.374 9.5			.512 13.0	.248 6.3	.134 3.4
	RVB5-6	RV5-6	1/4	.252 6.4	.472 12.0	.413 10.5	1.167 29.5			
	RVB5-8	RV5-8	5/16	.331 8.4	.591 15.0	.531 13.5	1.339 34.0			

100Y 编号	厂商编号	制造厂商	说明	护套颜色	尺寸 L*W*d2	压接线径	护套 全/半角	耐温°C/Volt/A	护套材质
6471	DRNY4-0.5		耐高温护套'R'型端子	黄色	4mm	26-22	半	105°C	Nylon
16615	RNYB8-8	KST	105°C端子 8AWG 62A	红色	37.3*15*8.4mm	8AWG(8mm2)	半	105°C/600V/62A	Nylon
11868	RNYBS8-6	KST	105°C端子 8AWG 62A	红色	31.3*12*6.4mm	8AWG(8mm2)	半	105°C/600V/62A	Nylon
4925	RV1-5	KST	护套中空圆形压线端子	RED	20.8*8*#10	22-16AWG(0.5-1.5mm2)	半角	75°C	VINYL
4928	RV1-6	KST	护套中空圆形压线端子	RED	26.8*11.6*1/4	22-16AWG(0.5-1.5mm2)	半角	75°C	VINYL
4930	RV2-6	KST	护套中空圆形压线端子	BLUE	26.8*12*1/4	16-14AWG(1.5-2.5mm2)	半角	75°C	VINYL
4951	RV3-4	KST	护套中空圆形压线端子	BLACK	25*8*#8	14-12AWG(2.5-4mm2)	半角	75°C	VINYL
4954	RV5-3.7	KST	护套中空圆形压线端子	YELLOW	22.7*7.2*#6	12-10AWG(4-6mm2)	半角	75°C	VINYL
4958	RV5-5	KST	护套中空圆形压线端子	YELLOW	26.6*9.5*#10	12-10AWG(4-6mm2)	半角	75°C	VINYL
4962	RV5-6	KST	护套中空圆形压线端子	YELLOW	29.5*12*1/4	12-10AWG(4-6mm2)	半角	75°C	VINYL
4278	RV5-8	KST	护套中空圆形压线端子	YELLOW	34*15*5/16	12-10AWG(4-6mm2)	半角	75°C	VINYL
4923	RVL1-4	KST	护套中空圆形压线端子	RED	20*8*#8	22-16AWG(0.5-1.5mm2)	半角	75°C	VINYL
4943	RVL2-4	KST	护套中空圆形压线端子	BLUE	21.8*8.5*#8	16-14AWG(1.5-2.5mm2)	半角	75°C	VINYL
4283	RVL5-4	KST	护套中空圆形压线端子	YELLOW	26.6*9.5*#8	12-10AWG(4-6mm2)	半角	75°C	VINYL
4921	RVS1-3.7	KST	护套中空圆形压线端子	RED	17.5*5.5*#6	22-16AWG(0.5-1.5mm2)	半角	75°C	VINYL
4948	RVS2-3.7	KST	护套中空圆形压线端子	BLUE	17.8*6.6*#6	16-14AWG(1.5-2.5mm2)	半角	75°C	VINYL
4945	RVS2-5	KST	护套中空圆形压线端子	BLUE	21.8*8.5*#10	16-14AWG(1.5-2.5mm2)	半角	75°C	VINYL

无护套子弹型公/母压线端子



OPEN BARREL TERMINALS (FEMALE & MALE)
 LR: LOOSE PIECE, STANDARD CHEMICAL TREATMENT (BRASS FINISH)
 LT: LOOSE PIECE, TIN PLATED
 SR: STRIP FORM, STANDARD CHEMICAL TREATMENT (BRASS FINISH)
 ST: STRIP FORM, TIN PLATED
 TERMINAL MATERIAL: BRASS



100Y 编号	厂商编号	说明	材质	尺寸 L*W(mm)	压接线径	公/母端子
11033	351LR	公裸端子 3.5φ	Brass Finish	16.4*3.5	16-14AWG(2mm2)	Male
11187	352LR	3.5φ母裸露端子	Brass Finish	17.3*3.5	16-14AWG(2mm2)	Female
10568	401LR	裸露公端子	Brass Finish	17.8*4.0	16-14AWG(2mm2)	Male
4276	402LR	母裸露端子	Brass Finish	17*3.95	16-14AWG(2mm2)	Female

ITEM NO	MATCHING	DIMENSION Inch mm			FIGURE
		W	F	L	
351LR	Φ3.5	.138 3.5	.331 8.4	.646 16.4	
352LR	Φ3.5	.138 3.5	.264 6.7	.681 17.3	
401LR	Φ4.0	.157 4.0	.331 8.4	.701 17.8	
402LR	Φ4.0	.156 3.95	.264 6.7	.669 17.0	

