




无护套叶片型公/母压线端子



OPEN BARREL TERMINALS (FEMALE & MALE)

LR: LOOSE PIECE, STANDARD CHEMICAL TREATMENT (BRASS FINISH)
 LT: LOOSE PIECE, TIN PLATED
 SR: STRIP FORM, STANDARD CHEMICAL TREATMENT (BRASS FINISH)
 ST: STRIP FORM, TIN PLATED
 TERMINAL MATERIAL: BRASS



Wire range A. W. G mm ²	ITEM NO	W	F	L	B	C
16-14A. W. G 1.5-2.5mm ²	MDN2-187(5)	.189 4.8	6.5	15	5.17	2.3




ITEM NO	MATCHING	DIMENSION W _{inch} mm	Q' TY BOX	FIGURE
606LR(5)	0.020x0.110 (0.5x2.8)	.126 3.2	1000	
606LR(8)	0.032x0.110 (0.8x2.8)	.126 3.2	1000	

100Y 编号	厂商编号	说明	材质	尺寸 L*W	压接线径	公/母端子
7825	501LR	公裸端子	Brass Finish	20*6.3	16-14AWG(2mm2)	Male
8768	503LR	镀金无护套端子	Breass Finish	19*6.6	16-14AWG(2mm2)	Female
10566	606LR(5)	镀金裸露母端子	Brass Finish	16*3.2mm	22-18AWG(1.25mm2)	Female
20039	606LT(8)	裸露母端子	Brass Finish-青铜	16*3.2mm	22-18AWG(1.25mm2)	Female
10570	906LR	镀金裸露公端子	Brass Finish	21*2.8mm	22-18AWG(1.25mm2)	Male
8766	FDN1-110(5)	无护套端子	Copper	W3.2	22-16AWG(0.5-1.5mm2)	Female
7944	FDN1-187(5)	无护套母端子	Copper	W5.0mm	22-16AWG(0.5-1.5mm2)	Female
4263	FDN1-250	裸端子	Copper	W6.6mm	22-16AWG(0.5-1.5mm2)	Female
12181	FDN2-110(5)	无护套裸端子	Copper	W3.2mm	16-14AWG(1.5-2.5mm2)	Female
7832	FDN2-187(5)	裸端子	Copper	W5.0mm	16-14AWG(1.5-2.5mm2)	Female
7830	FDN2-250	裸端子	Copper	W6.6mm	16-14AWG(1.5-2.5mm2)	Female
7952	MDN2-187(5)	无护套公端子	Copper	14.2*4.8mm	16-14AWG(1.5-2.5mm2)	Male

详细产品规格 - 请点击 cn.100y.com.tw

ITEM NO	MATCHING	DIMENSION Inch mm			FIGURE
		W	F	L	
501LR	.032x.250 (0.8x6.4)	.248 6.3	.295 7.5	.787 20.0	
503LR		.260 6.6	.295 7.5	.748 19.0	



Wire range A. W. G mm ²	ITEM NO	W	F	L	B	C
22-16A. W. G 0.5-1.5mm ²	FDN1-110(5)	3.86	6.32	13.6	5.21	1.7
	FDN1-187(5)	5.0	6.4	15	5.0	1.7
	FDN1-250	6.6	7.3	16	5.2	1.7
16-14A. W. G 1.5-2.5mm ²	FDN2-110(5)	3.2	6.5	13.6	5.14	2.3
	FDN2-187(5)	5.0	6.4	15	5.06	2.3
	FDN2-250	5.0	6.4	15	5.06	2.3

无护套 'Y' 形压线端子



NON-INSULATED SPADE TERMINALS

MAXIMUM ELECTRIC CURRENT:

22~16 A.W.G.:19 AMPERE

16~14 A.W.G.:27 AMPERE

14-12 A.W.G.:37 AMPERE


12-10 A.W.G.:48 AMPERE

8 A.W.G.:62 AMPERE

6 A.W.G.:88 AMPERE

TERMINAL MATERIAL:

COPPER



Wire range A. W. G mm ²	ITEM NO	BRAZED SEAM	NO BUTTED SEAM	STUD SIZE D2	DIMENSION Inch mm							
					W	F	L	E	D	d1	T	
22-16 A. W. G. 0.5-1.5mm ²	SNBS1-3.7	SNS1-3.7	#6	.146 3.7	.323 5.7							
	SNBM1-4	SNM1-4	#8	.169 4.3	.283 7.2	.256 6.5	.630 16.0	.189 4.8	.134 3.4	.067 1.7	.030 0.75	
	SNBL1-5	SNL1-5	#10	.209 5.3	.374 9.5							
16-14 A. W. G. 1.5-2.5mm ²	SNBS2-3.7	SNS-3.7	#6	.146 3.7	.224 5.7							
	SNBM2-4	SNM2-4	#8	.169 4.3	.283 7.2	.256 6.5	.630 16.0	.189 4.8	.161 4.1	.091 2.3	.031 0.8	
	SNBL2-5	SNL2-5	#10	.209 5.3	.366 9.3							
14-12 A. W. G. 2.5-4mm ²	SNB3-4	SN3-4	#8	.169 4.3	.315 8.0	.276 7.0	.720 18.3	.236 6.0	.199 5.0	.188 3.0	.039 1.0	
	SNB3-5	SN3-5	#10	.209 5.3	.354 9.0	.276 7.0	.728 18.5	.236 6.0	.220 5.6	.134 3.4	.039 1.0	
12-10 A. W. G. 4-6mm ²	SNBL5-4	SNL5-4	#8	.169 4.3	.354 9.0	.276 7.0	.728 18.5	.236 6.0	.220 5.6	.134 3.4	.039 1.0	
	SNBL5-5	SN5-5	#10	.209 5.3	.354 9.0	.276 7.0	.728 18.5	.236 6.0	.220 5.6	.134 3.4	.039 1.0	
	SNBL5-6	SN5-6	1/4	.472 6.4	.472 12.0	.965 24.5						

100Y 编号	厂商编号	制造厂商	说明	材质	L*W*D*d1*d2 (mm)	压接线径	Ampere
8299	SNB3-4	KST	"Y"裸端子	Copper	18.3*8.0*5.0*3.0*4.3	14-12AWG(2.5-4mm2)	37A
10481	SNB3-5	KST	"Y"裸端子	Copper	18.3*8.0*5.0*3.0*5.3	14-12AWG(2.5-4mm2)	37A
4265	SNB5-5	KST	"Y"裸端子	Copper	18.5*9.0*5.6*3.4*5.3	12-10AWG(4-6mm2)	48A
10482	SNBL1-5	KST	"Y"裸端子	Copper	16*9.5*3.4*1.7*5.3	22-16AWG(0.5-1.5mm2)	19A
7988	SNBL2-5	KST	"Y"裸端子	Copper	16*9.3*4.1*2.3*5.3	16-14AWG(1.5-2.5mm2)	27A
10455	SNBL5-4	KST	"Y"裸端子	Copper	18.5*9.0*5.6*3.4*4.3	12-10AWG(4-6mm2)	48A
7954	SNBL5-6	KST	"Y"裸端子	Copper	24.5*12*5.6*3.4*6.4	12-10AWG(4-6mm2)	48A
5520	SNBM1-4	KST	"Y"裸端子	Copper	16*7.2*3.4*1.7*4.3	22-16AWG(0.5-1.5mm2)	19A
8301	SNBM2-4	KST	"Y"裸端子	Copper	16*7.2*4.1*2.3*4.3	16-14AWG(1.5-2.5mm2)	27A
5623	SNBS1-3.7	KST	"Y"裸端子	Copper	16*5.7*3.4*1.7*3.7	22-16AWG(0.5-1.5mm2)	19A
2861	SNBS2-3.7	KST	"Y"裸端子	Copper	16*5.7*4.1*2.3*3.7	16-14AWG(1.5-2.5mm2)	27A
17829	Y1.25-4	KST	Y型裸端子			22-16AWG	
17830	Y2-4	KST	Y型裸端子			16-14AWG	
17831	Y3.5-5	KST	Y型裸端子			14-12AWG	
17880	Y5.5-5	KST	Y型裸端子			12-10AWG	
17932	Y8-5	KST	Y型裸端子		24*12*5.3	8AWG(10mm)	

