



无护套“R”圆型压线端子



COPPER TUBULAR LUGS

MAXIMUM ELECTRIC CURRENT:
12-10A.W.G.:48 AMPERE
8A.W.G.:90 AMPERE
6A.W.G.:125 AMPERE
4A.W.G.:160 AMPERE
1/0A.W.G.:250 AMPERE
2/0A.W.G.:310 AMPERE
TERMINAL MATERIAL: COPPER TUBULAR




Table with columns: Wire range, ITEM NO, DIMENSION (Inch, mm) and rows for TLK25-5 and TLK25-6



NON-INSULATED SQUARE TONGUE TERMINALS

MAXIMUM ELECTRIC CURRENT:
4A.W.G.:115 AMPERE
2A.W.G.:160 AMPERE
1/0A.W.G.:215 AMPERE
3/0A.W.G.:255 AMPERE
4/0A.W.G.:300 AMPERE
250/300 MCM A.W.G.:395 AMPERE
400/500 MCM A.W.G.:470 AMPERE
TERMINAL MATERIAL: COPPER




Table with columns: Wire range, ITEM NO, STUD SIZE, DIMENSION (Inch, mm) and rows for SQNBS22-5



Table with columns: 型号, 螺丝孔, 尺寸, Wire Size and rows for R80-12, R100-12, R125-12

Main product specification table with columns: 100Y 编号, 厂商编号, 说明, Ampere, L*W*D*d1*d2 (mm), 压接线径, 材质

详细产品规格 - 请点击cn.100y.com.tw



NON-INSULATED RING TERMINALS

MAXIMUM ELECTRIC CURRENT:
22~16A.W.G.:19 AMPERE
16~14A.W.G.:27 AMPERE
14-12A.W.G.:37 AMPERE
12-10A.W.G.:48 AMPERE
8A.W.G.:62 AMPERE
6A.W.G.:88 AMPERE
4A.W.G.:115 AMPERE
2A.W.G.:160 AMPERE
TERMINAL MATERIAL: COPPER





Table with columns: Wire range, ITEM NO, BUTTED SEAM, STUD SIZE, DIMENSION (Inch, mm) and rows for RNBS1-3.7, RNBL1-4, RNB1-5, RNB1-6, RNBS2-3.7, RNBL2-4, RNBS2-5, RNBS3-4, RNBS3-5, RNBL5-4, RNBS5-4, RNBS5-8, RNBS8-6, RNB22-10

端子绝缘护套(PVC)



FLAT INSULATING SLEEVES



MATERIAL: SOFT P. V. C
COLOR: NATURAL / BLUE (耐高温)
UNIT: mm
用途: 用于端子压著后端子与外界间之绝缘。

SERIES-110

Table with columns: PART NO, W, D, L, WIRE SIZE (O. D) and rows for 64020, 64025, 64030, 64035

Table with columns: 100Y 编号, 厂商编号, 尺寸 D1*D2, 说明, For 端子 sq and rows for 10553, 5160, 5135

详细产品规格 - 请点击cn.100y.com.tw

