



DC 风扇

详细产品规格 - 请点击 cn.100y.com.tw

UL1571 #26AWG +RED, -BLACK

ROTATION

AIR FLOW

PAT.

CE

10±0.5

SUNON.

KDE0501PFB3-8 GM0502PFV3-8

- 0.43 to 0.65 CFM
- 5 VDC (nominal)
- Patented Single-coil Brushless 8 Poles DC Motor Design
- Locked Rotor Protection
- Low Power Consumption
- Precision Ball Bearing System
- 28 AWG UL Rating Leadwire, "+" Red and "-" Black
- UL, CUR & TUV Approval

UL2468 #26AWG +RED, -BLACK

ROTATION

AIR FLOW

300±0.5

5±1

3-#2.5

150±0.30

16.2±0.3

20±0.50

32±0.3

50±0.5

4-#4.3

3±0.3

10.5±0.5

UNIT:mm

SUNON.

KD2405PFB1-8

- 7.0 to 10.2 CFM
- 5 and 12 VDC (nominal)
- Patented Single-coil Brushless 8 Poles DC Motor Design
- Locked Rotor Protection
- Low Power Consumption
- Polarity Protected
- Lubricated Sintered Sleeve Bearing System or Precision Ball Bearing System
- 26 AWG UL Rating Leadwire, "+" Red and "-" Black
- UL, CUR & TUV Approval

100Y 编号	厂商编号	制造厂商	说明	尺寸(mm)	电压	r.p.m	电流(A)	Watts	Air Flow(CFM)	Noise (dBA)	Ball/Sleeve
29359	GM0502PFV3-8	SUNON	风扇带线式	25*25*10	5V	7000	0.04	0.2	2.3	9.5	VAPO
15961	KD2405PFB1-8	SUNON	风扇带线式	50*50*10	24V	5100	0.04A	1.0W	9	30	Ball
3895	KDE0501PFB3-8	SUNON	风扇带线式	20*20*10	5	1000	0.1	0.3	0.65	30	Ball

UL1007 #24AWG +RED, -BLACK

ROTATION

AIR FLOW

300±0.5

5±1

82.5±0.3

92±0.5

4±0.3

25.5±0.5

8-#4.3

SUNON.

KD1209PTB1 KD1209PTS1-H

- 39 to 51 CFM
- 12 and 24 VDC (nominal)
- Patented Single-coil Brushless DC Motor Design
- Locked Rotor Protection
- Available with 4 Poles Motor or 6 Poles Motor
- Locked Rotor Protection
- Polarity Protected
- Lubricated Sintered Sleeve Bearing System or Precision Ball Bearing System
- 24 AWG UL Rating Leadwire, "+" Red and "-" Black
- UL, CUR & TUV Approval

UL1007 #24AWG +RED, -BLACK

ROTATION

AIR FLOW

300±0.5

5±1

82.5±0.3

92±0.5

4±0.3

25.5±0.5

8-#4.3

SUNON.

KD1208PTB1
KD1208PTS3.H.M
KD1208PTB3-6(OCM)
KD2408PTB1-13.2.A

- 29.4 to 42.5 CFM
- 12 or 24 VDC (nominal)
- Patented Single-coil Brushless DC Motor Design
- Available with 4 Poles or 6 Poles Motor
- Locked Rotor Protection
- Polarity Protection
- Lubricated Sintered Sleeve Bearing System or Precision Ball Bearing System
- 24 AWG UL Rating Leadwire, "+" Red and "-" Black
- UL, CUR & TUV Approval

100Y 编号	厂商编号	制造厂商	说明	尺寸(mm)	电压	r.p.m	电流(A)	Watts	Air Flow(CFM)	Noise (dBA)	Ball/Sleeve
12106	KD1208PTB1	SUNON	风扇带线式	80*80*25	12V	3000		2.5W	39.5	33	Ball
14867	KD1208PTB3-6(OCM)	SUNON	风扇带线式	80*80*25	12V	2500	0.12	1.4	30	28.5	Ball
16506	KD1208PTS3.H.M	SUNON	风扇带线式	80x80x25	12V	2300	0.12A	1.4W	31	25	Sleeve Bearing
12104	KD1209PTB1	SUNON	风扇带线式	92*92*25	12V	2700		2.5	49	34.5	Ball
16804	KD1209PTS1-H	SUNON	风扇带线式	92*92*25mm	12Vdc	2500		2.6W	45.5	33	Sleeve
27640	KD2408PTB1-13.2.A	SUNON	风扇带线式	80*80*25	24V	3100	0.07A	1.7W	41	35	Ball

UL1007 #26AWG +RED, -BLACK

ROTATION

AIR FLOW

300±0.5

5±1

50±0.3

60±0.5

4±0.3

25.5±0.5

8-#4.3

SUNON.

KD1206PFS1-H.G
KD1206PTS1.13
KD1206PTB1

- 15.9 to 22.1 CFM
- 12 and 24 VDC (nominal)
- Patented Single coil Brushless 4 Poles DC Motor Design
- Locked Rotor Protection
- Polarity Protected
- Lubricated Sintered Sleeve Bearing System or Precision Ball Bearing System
- 26 AWG UL Rating Leadwire, "+" Red and "-" Black
- UL, CUR & TUV Approval

UL1571 #26AWG +RED, -BLACK

ROTATION

AIR FLOW

300±0.5

5±1

50

55

50

55

3-#2.5

PAT.

CE

10±0.5

SUNON.

KD1255PFS1-F.G

Part No	Dimensions (mm)	Model (VDC)	Voltage Input (watts)	Speed (RPM)	Air flow (CFM)	Static pressure (Inch-H2O)	Noise (dBA)
1785	55x55x10	Kd1255PFS1-F.G	12V	1.4	5700	15.0	0.16

100Y 编号	厂商编号	制造厂商	说明	尺寸(mm)	电压	r.p.m	电流(A)	Watts	Air Flow(CFM)	Noise (dBA)	Ball/Sleeve
1786	KD1206PFS1-H.G	SUNON	风扇带线式	60*60*10mm	12Vdc	5200		1.4W	16.5	35	Sleeve
17341	KD1206PTB1	SUNON	"SUNON" DC 带线式风扇	60*60*25mm	12	5100	0.19	2.2	22.1	34.3	Ball Bearing
23834	KD1206PTS1.13	SUNON	"SUNON" DC 带线式风扇	60*60*25mm	12	4500	0.19	1.6	21.7	34	Sleeve
1785	KD1255PFS1-F.G	SUNON	风扇带线式	55*55*10mm	12Vdc	5700		1.4W	15	36	Sleeve

