



保险丝+电路保护器

Bussmann_S5XX 系列保险丝

详细产品规格 - 请点击 cn.100y.com.tw



- 作用快
- 高遮断电容
- 物理规格: 0.197" x 0.788" (5mm x 20mm)
- 建材: Ceramic tube End caps: nickel or silver plated brass
- Voltage Rating: 250V AC or less
- IR: 1500A
- Agency Information: See BIF document for specifics VDE, SEMKO, IMQ, UL

100Y 编号	厂商编号	制造厂商	说明	电容量 (A)	电压	IR (A)	规格
10102	MIF-0.25A	Bussmann	Fast-Acting 快溶陶瓷保险丝	0.25A	250V		5*20mm
12476	MIF-1.5A	Bussmann	Fast-Acting 快溶陶瓷保险丝	1.5A	250V		5*20mm
42934	S500-4A	Bussmann	S500 Series, Fast Acting, Glass Tube	35A	250V	4A	5.2*20
10093	S501-0.125A	Bussmann	Fast-Acting 快溶陶瓷保险丝	0.125	250V		5*20mm
10092	S501-0.16A	Bussmann	Fast-Acting 快溶陶瓷保险丝	0.16	250V		5*20mm
10099	S501-0.1A	Bussmann	Fast-Acting 快溶陶瓷保险丝	0.1A	250V		5*20mm
10094	S501-0.2A	Bussmann	Fast-Acting 快溶陶瓷保险丝	0.2A	250V		5*20mm
10095	S501-0.315A	Bussmann	Fast-Acting 快溶陶瓷保险丝	0.315	250V		5*20mm
10104	S501-0.5A	Bussmann	Fast-Acting 快溶陶瓷保险丝	0.5A	250V		5*20mm
10103	S501-0.63A	Bussmann	Fast-Acting 快溶陶瓷保险丝	0.63A	250V		5*20mm
10098	S501-1.25A	Bussmann	Fast-Acting 快溶陶瓷保险丝	1.25A	250V		5*20mm
6117	S501-1.6A	Bussmann	Fast-Acting 快溶陶瓷保险丝	1.6A	250V		5*20mm
10096	S501-1A	Bussmann	Fast-Acting 快溶陶瓷保险丝	1A	250V		5*20mm
10097	S501-2.5A	Bussmann	Fast-Acting 快溶陶瓷保险丝	2.5A	250V		5*20mm
12477	S501-20A	Bussmann	Fast-Acting 快溶陶瓷保险丝	20A	250V		5*20mm
2225	S501-2A	Bussmann	Fast-Acting 快溶陶瓷保险丝	2A	250V		5*20mm
6116	S501-3.15A	Bussmann	Fast-Acting 快溶陶瓷保险丝	3.15A	250V		5*20mm
10100	S501-4A	Bussmann	Fast-Acting 快溶陶瓷保险丝	4A	250V		5*20mm
10101	S501-5A	Bussmann	Fast-Acting 快溶陶瓷保险丝	5A	250V		5*20mm
6119	S501-6.3A	Bussmann	Fast-Acting 快溶陶瓷保险丝	6.3A	250V		5*20mm




S504-0.05A



5x20mm IEC MINATURE FUSE LINKS
 TIME-DELAY
 LOW BREAKING CAPACITY
 250 VOLTS AC or less
 U. L. RECOGNIZED, GUIDE JDYX2, File E75865
 DESIGNED TO IEC (PUB127) SHEET III

- 包装: 100
- 重量: 1000=0.785kg
- 只允许用于大包装
- 实例: BK/S504-1A



100Y 编号	厂商编号	制造厂商	说明	电容量 (A)	电压	IR (A)	规格
28057	S504-0.05A	Bussmann	S504 欧规慢熔玻璃管保险丝	0.05A (50mA)	250V	35A ac	5*20mm




S505-1.6A



- 种类:**
- 用时长, 高遮断电容
 - 5mmx20mm 物理规格
 - 瓷管, 镀镍铜罩外包
 - 可选轴心线 .032" x 1.5" 铜端子
 - 由 IEC 设计 60127-2 (1A-6.3A)
- 分类:**
- 特殊生产密码, 选项密码和包装密码

- 代理资料:**
- UL Recognized Card: (1A-6.3A) guide JDYX2 File E19180
 - Semko Approval, 1A-6.3A
 - VDE Approval, 1.25A-5A
 - BSI Approval, 1.25A-6.3
 - IMQ Approval, 1.25A-6.3A
 - MITI Approval, 1A-6.3A




100Y 编号	厂商编号	制造厂商	说明	电容量 (A)	电压	IR (A)	规格
41255	S505-1.6A	Bussmann	Time Delay Ceramic Tube Fuse	1.6A	250V	1500A	5*20mm



- 种类:**
- 用时长, 高遮断电容
 - 5mmx20mm 物理规格
 - 瓷管, 镀镍铜罩外包
 - 可选轴心线 .032" x 1.5" 铜端子
 - 由 IEC 设计 60127-2 (1A-6.3A)
- 分类:**
- 特殊生产密码, 选项密码和包装密码

- 代理资料:**
- UL Recognized Card: (1A-6.3A) guide JDYX2 File E19180
 - Semko Approval, 500mA-6.3A
 - VDE Approval, 500mA-5A
 - BSI Approval, 500mA-6.3
 - IMQ Approval, 800mA-6.3A
 - MITI Approval, 1A-6.3A



100Y 编号	厂商编号	制造厂商	说明	电容量 (A)	电压	IR (A)	规格
27983	S506-1.25A	Bussmann	S506 欧规慢熔玻璃管保险丝	1.25A	250V	35Aac	5*20mm



服务专线: 台湾: 886-3-5753170
 传 真: 台湾: 886-3-5753172
 E-mail: 台湾: sale@100y.com.tw

深圳: 86-755-83298787
 深圳: 86-755-83640655
 深圳: 100y@163.com

上海: 86-21-34970699
 上海: 86-21-64605107
 上海: 100y-1@163.com