



IWASAKI_仪器用灯泡

详细产品规格 - 请点击 cn.100y.com.tw




Type	Reference or Substitute Lamp	Volts (V)	Watts (W)	Colour Temp (k)	Rated Av. life (hrs)	Dimensions (mm)		Base	Filament	Fig. No.
						M. D.	M.O.L			
JCR15V150W/G1	EFR	15	150	3400	50	50.5	42.0	GZ6.35	C-8	4

Part No.	Product No.	Manufacturer	Description	Voltage (V)	Watts (W)	Color(K)	Filament Design	Ave. Life (hr)	ANSI
31716	IWASAKI-JCR15V150W/G1	IWASAKI	IWASAKI_Projection Lamp	15V	150W	3400K	GZ6.35	50hr.	EFR




Type	Reference or Substitute Lamp	Volts (V)	Watts (W)	Colour Temp (k)	Rated Av. life (hrs)	Dimensions (mm)		Base	Filament	Fig. No.
						M. D.	M.O.L			
JCR15V150W5H/G1	—	15	150	3200	500	50.5	42.0	GZ6.35	C-8	4

Part No.	Product No.	Manufacturer	Description	Voltage (V)	Watts (W)	Color(K)	Filament Design	Ave. Life (hr)
31717	IWASAKI-JCR15V150W5H/G1	IWASAKI	IWASAKI_Projection Lamp	15V	150W	3200K	GZ6.35	500hr.




Type	Reference or Substitute Lamp	Volts (V)	Watts (W)	Colour Temp (k)	Rated Av. life (hrs)	Dimensions (mm)		Base	Filament	Fig. No.
						M. D.	M.O.L			
JCR19.5V150W/G2	—	19.5	150	3250	150	50.5	44.5	GX5.3	CC-6	4

Part No.	Product No.	Manufacturer	Description	Voltage (V)	Watts (W)	Color(K)	Filament Design	Ave. Life (hr)
31710	IWASAKI-JCR19.5V150W/G2	IWASAKI	IWASAKI_Projection Lamp	19.5V	150W	3250K	GX5.3	150hr.




Type	Reference or Substitute Lamp	Volts (V)	Watts (W)	Colour Temp (k)	Rated Av. life (hrs)	Dimensions (mm)		Base	Filament	Fig. No.
						M. D.	M.O.L			
JCR24V150W10H/G2/H50	—	24	150	3200	1000	50.5	44.5	GX5.3	CC-6	4

Part No.	Product No.	Manufacturer	Description	Voltage (V)	Watts (W)	Color(K)	Filament Design	Ave. Life (hr)
31719	IWASAKI-JCR24V150W10H/G2/H50	IWASAKI	IWASAKI_Projection Lamp	24V	150W	3200K	GX5.3	1000hr.




Type	Reference or Substitute Lamp	Volts (V)	Watts (W)	Colour Temp (k)	Rated Av. life (hrs)	Dimensions (mm)		Base	Filament	Fig. No.
						M. D.	M.O.L			
JCR24V200W10H/G2/H50-D	—	24	200	3200	1000	50.5	44.5	GX5.3	CC-6	4

Part No.	Product No.	Manufacturer	Description	Voltage (V)	Watts (W)	Color(K)	Filament Design	Ave. Life (hr)
31720	IWASAKI-JCR24V200W10H/G2/H50-D	IWASAKI	IWASAKI_Projection Lamp	24V	200W	3200K	GX5.3	1000hr.




Type	Reference or Substitute Lamp	Volts (V)	Watts (W)	Colour Temp (k)	Rated Av. life (hrs)	Dimensions (mm)		Base	Filament	Fig. No.
						M. D.	M.O.L			
JCR6V10W20H/2GZ	—	6	10	2900	2000	25.3	31.6	GZ4	C-8	1

Part No.	Product No.	Manufacturer	Description	Voltage (V)	Watts (W)	Color(K)	Filament Design	Ave. Life (hr)
31688	IWASAKI-JCR6V10W20H/2GZ	IWASAKI	IWASAKI_Projection Lamp	6V	10W	2900K	GZ4	2000hr.



Type	Reference or Substitute Lamp	Volts (V)	Watts (W)	Colour Temp (k)	Rated Av. life (hrs)	Dimensions (mm)		Base	Filament	Fig. No.
						M. D.	M.O.L			
JCR6V50W20H/G1	—	6	50	3000	2000	50.0	44.0	GZ6.35	C-8	3
JCR9.5V55W15H/G1	—	9.5	55	3000	1500	50.0	42.0	GZ6.35	C-8	3

Part No.	Product No.	Manufacturer	Description	Voltage (V)	Watts (W)	Color(K)	Filament Design	Ave. Life (hr)
31696	IWASAKI-JCR6V50W20H/G1	IWASAKI	IWASAKI_Projection Lamp	6V	50W	3000K	GZ6.35	2000hr.
31699	IWASAKI-JCR9.5V55W15H/G1	IWASAKI	IWASAKI_Projection Lamp	9.5V	55W	3000K	GZ6.35	1500hr.



Type	Reference or Substitute Lamp	Volts (V)	Watts (W)	Approx Initial Lumens (lm)	Colour Temp (k)	Rated Av. life (hrs)	Dimensions (mm)			Base	Filament	Fig. No.
							M. D.	M.O.L	L.C.L			
JCR9.5V55W15H/G1	—	9.5	55	—	3000	1500	50.0	42	—	G6.35	C-8	1A

Part No.	Product No.	Manufacturer	Description	Voltage (V)	Watts (W)	Color(K)	Filament Design	Ave. Life (hr)
31805	IWASAKI-JCR9.5V55W15H/G1	IWASAKI	IWASAKI_Projection Lamp	9.5V	55W	3000K	GZ6.35	1500hr.



服务专线: 台湾: 886-3-5753170
 传 真: 台湾: 886-3-5753172

E-mail: sale@100y.com.tw

深圳: 86-755-83298787
 深圳: 86-755-83640655
 深圳: 100y@163.com

上海: 86-21-34970699
 上海: 86-21-64605107
 上海: 100y-1@163.com