



30AWG 绕线用银线

详细产品规格 - 请点击 cn.100y.com.tw



| ROLL SIZE AWG | 30 | 28 | 26 | 24 |
|--------------------------------|--|--------|--------|--------|
| BOND STRENGTH (LBS.) | 2.0MAX | 3.5MAX | 4.0MAX | 5.0MAX |
| CONDUCTOR RESISTANCE Ω/100 FT | 105.1 | 66.2 | 41.6 | 26.2 |
| CONDUCTOR MATERIAL | SILVER COATED COPEER | | | |
| INSULATION MATERIAL | "KYNAR"(COMPOUND OF POLYVINYLIDENE FLUORIDE) | | | |
| TEST VOLTAGE (INSULATION) | 2,000 VOLTS FOR 1 MINUTE, RMS | | | |
| VOLTAGE RATING | 150V | | | |
| TEMPERATURE RATING | 105°C | | | |
| ELONGATION OF INSULATION | 250% (MIN) | | | |
| ELONGATION OF CONDUCTOR | 20% (MIN) | | | |
| TENSILE STRENGTH OF INSULATION | 5,000 PSI (MIN) | | | |
| TENSILE STRENGTH OF CONDUCTOR | 40,000 PSI (MAX) | | | |
| INSULATION RESISTANCE | 1,930 MEGOHMS FOR 1,000 FT (MIN) | | | |
| CONCENTRICITY | 80% | | | |
| MILITARY SPEC. | MIL-W 81822/13 | | | |

| 100Y 编号 | 厂商编号 | 说明 | Color | Length (Feet) | Temp. Rating | Volt. Rating |
|---------|------------|-----------|-------|---------------|--------------|--------------|
| 12781 | K30-100-B | 银线 #30 黑色 | 黑色 | 100Feet/R | 105°C | 150V |
| 12641 | K30-100-BL | 银线 #30 蓝色 | 蓝色 | 100Feet/R | 105°C | 150V |
| 12643 | K30-100-G | 银线 #30 绿色 | 绿色 | 100Feet/R | 105°C | 150V |
| 12778 | K30-100-R | 银线 #30 红色 | 红色 | 100Feet/R | 105°C | 150V |
| 12780 | K30-100-W | 银线 #30 白色 | 白色 | 100Feet/R | 105°C | 150V |
| 12783 | K30-100-Y | 银线 #30 黄色 | 黄色 | 100Feet/R | 105°C | 150V |
| 27073 | K30-100-灰 | 银线 #30 灰色 | 灰色 | 100Feet/R | 105°C | 150V |
| 12779 | K30-100-桔 | 银线 #30 桔色 | 橙色 | 100Feet/R | 105°C | 150V |
| 27075 | K30-100-棕 | 银线 #30 棕色 | 棕色 | 100Feet/R | 105°C | 150V |
| 12782 | K30-100-紫 | 银线 #30 紫色 | 紫色 | 100Feet/R | 105°C | 150V |
| 23668 | K30-500-棕 | 银线 #30 棕色 | 棕色 | 500Feet/R | 105°C | 150V |
| 14807 | K30-500-B | 银线 #30 黑色 | 黑色 | 500Feet/R | 105°C | 150V |
| 14374 | K30-500-BL | 银线 #30 蓝色 | 蓝 | 500Feet/R | 105°C | 150V |
| 14651 | K30-500-G | 银线 #30 绿色 | 绿色 | 500Feet/R | 105°C | 150V |
| 14808 | K30-500-R | 银线 #30 红色 | 红色 | 500Feet/R | 105°C | 150V |
| 14652 | K30-500-W | 银线 #30 白色 | 白色 | 500Feet/R | 105°C | 150V |
| 14373 | K30-500-Y | 银线 #30 黄色 | 黄色 | 500Feet/R | 105°C | 150V |
| 23667 | K30-500-灰 | 银线 #30 灰色 | 灰色 | 500Feet/R | 105°C | 150V |
| 22513 | K30-500-紫 | 银线 #30 紫色 | 紫色 | 500Feet/R | 105°C | 150V |
| 23669 | K30-500-橙 | 银线 #30 橙色 | 橙色 | 500Feet/R | 105°C | 150V |

30 AWG (0.25MM) INSULATION DIAMETER 0.0195" (0.50MM) UL1423



| Roll Size | White | Yellow | Blue | Red | Green | Black |
|-----------------------|------------|------------|-------------|------------|------------|------------|
| 500ft. (152.0M) ROLL | R30-500-W | R30-500-Y | R30-500-BL | R30-500-R | R30-500-G | R30-500-B |
| 1000ft. (304.0M) ROLL | R30-1000-W | R30-1000-Y | R30-1000-BL | R30-1000-R | R30-1000-G | R30-1000-B |

注：另外的颜色和更大的卷大小也许取得到，请与工厂联系为细节

| ROLL SIZE AWG | 30 | 28 | 26 | 24 |
|-------------------------------|------------|-------------|-------------|-------------|
| UL STYLE UL | 1423 | 1422 | 1422 | 1423 |
| OTHER DIAMETER | 0.50MM | 0.60MM | 0.70MM | 0.76MM |
| CONDUCTOR DIAMETER | 0.25MM | 0.32MM | 0.40MM | 0.50MM |
| INSULATION THICKNESS | 0.005" NOM | 0.0055" NOM | 0.0057" NOM | 0.0055" NOM |
| CONDUCTOR-TO-INSULATION | 0.5MIN | 0.5MIN | 1.0MIN | 1.0MIN |
| BOND STRENGTH (LBS.) | 2.0MAX | 3.5MAX | 4.0MAX | 5.0MAX |
| CONDUCTOR RESISTANCE Ω/100 FT | 105.1 | 66.2 | 41.6 | 26.2 |



服务专线:台湾:886-3-5753170

传 真:台湾:886-3-5753172

E-mail:台湾:sale@100y.com.tw

深圳:86-755-83298787

深圳:86-755-83640655

深圳:100y@163.com

上海:86-21-34970699

上海:86-21-64605107

上海:100y-1@163.com