



PC板+感光系统+PCB电钻

28AWG 绕线用银线

详细产品规格 - 请点击 cn.100y.com.tw



ROLL SIZE AWG	30	28	26	24
BOND STRENGTH (LBS.)	2.0MAX	3.5MAX	4.0MAX	5.0MAX
CONDUCTOR RESISTANCE Ω/100 FT	105.1	66.2	41.6	26.2
CONDUCTOR MATERIAL	SILVER COATED COPEER			
INSULATION MATERIAL	"KYNAR"(COMPOUND OF POLYVINYLIDENE FLUORIDE)			
TEST VOLTAGE (INSULATION)	2,000 VOLTS FOR 1 MINUTE, RMS			
VOLTAGE RATING	150V			
TEMPERATURE RATING	105°C			
ELONGATION OF INSULATION	250% (MIN)			
ELONGATION OF CONDUCTOR	20% (MIN)			
TENSILE STRENGTH OF INSULATION	5,000 PSI (MIN)			
TENSILE STRENGTH OF CONDUCTOR	40,000 PSI (MAX)			
INSULATION RESISTANCE	1,930 MEGOHMS FOR 1,000 FT (MIN)			
CONCENTRICITY	80%			
MILITARY SPEC.	MIL-W 81822/13			

100Y 编号	厂商编号	说明	Color	Length (Feet)	Temp. Rating	Volt. Rating
32928	K28-500-橙	银线 #28 橙色	橙色	500Feet/R	105°C	150V
37749	KP-28F-200-R	银线 #28 红色	红色	200Feet/R	105°C	150V
37748	KP-28F-200-棕	银线 #28 棕色	棕色	200Feet/R	105°C	150V
37746	KP-28F-200-橙	银线 #28 橙色	橙色	200Feet/R	105°C	150V
39517	KP-28F-500-W	银线 #28 白色	白色	500Feet/R	105°C	150V
11545	R-500-28-B	银线 #28 黑色	黑色	500Feet/R	105°C	150V
7685	R-500-28-BL	银线 #28 蓝色	蓝色	500Feet/R	105°C	150V
2137	R-500-28-G	银线 #28 绿色	绿色	500Feet/R	105°C	150V
7686	R-500-28-R	银线 #28 红色	红色	500Feet/R	105°C	150V
7687	R-500-28-Y	银线 #28 黄色	黄色	500Feet/R	105°C	150V
28959	R28B-1000	Kynar_银线 #28 蓝色	蓝色	1000Feet/R	105°C	150V
28526	R28BLK-1000	Kynar_银线 #28 黑色	黑色	1000Feet/R	105°C	150V
28962	R28G-1000	Kynar_银线 #28 绿色	绿色	1000Feet/R	105°C	150V
28960	R28Gray-1000	Kynar_银线 #28 灰色	灰色	1000Feet/R	105°C	150V
28520	R28R-1000	Kynar_银线 #28 白色	白色	1000Feet/R	105°C	150V
28525	R28W-1000	Kynar_银线 #28 白色	白色	1000Feet/R	105°C	150V
28961	R28Y-1000	Kynar_银线 #28 黄色	黄色	1000Feet/R	105°C	150V

26AWG 绕线用银线

详细产品规格 - 请点击 cn.100y.com.tw



26 AWG (0.40MM) INSULATION DIAMETER 0.027" (0.69MM) UL1422

Roll Size	White	Yellow	Blue	Red	Green	Black
500Ft. (152.0M) ROLL	R26-500-W	R26-500-Y	R26-500-BL	R26-500-R	R26-500-G	R26-500-B
1000Ft. (304.0M) ROLL	R26-1000-W	R26-1000-Y	R26-1000-BL	R26-1000-R	R26-1000-G	R26-1000-B

注：另外的颜色和更大的卷大小也许取得到，请与工厂联系为细节

ROLL SIZE AWG	30	28	26	24
UL STYLE UL	1423	1422	1422	1423
OTHER DIAMETER	0.50MM	0.60MM	0.70MM	0.76MM
CONDUCTOR DIAMETER	0.25MM	0.32MM	0.40MM	0.50MM
INSULATION THICKNESS	0.005" NOM	0.0055" NOM	0.0057" NOM	0.0055" NOM
CONDUCTOR-TO-INSULATION	0.5MIN	0.5MIN	1.0MIN	1.0MIN
BOND STRENGTH (LBS.)	2.0MAX	3.5MAX	4.0MAX	5.0MAX
CONDUCTOR RESISTANCE Ω/100 FT	105.1	66.2	41.6	26.2
CONDUCTOR MATERIAL	SILVER COATED COPEER			



服务专线: 台湾: 886-3-5753170

传 真: 台湾: 886-3-5753172

E-mail: 台湾: sale@100y.com.tw

深圳: 86-755-83298787

深圳: 86-755-83640655

深圳: 100y@163.com

上海: 86-21-34970699

上海: 86-21-64605107

上海: 100y-1@163.com