



# 电源供应器+转换器+UPS

## 55W~250W 可充电-单组电源供应器

详细产品规格 - 请点击 [cn.100y.com.tw](http://cn.100y.com.tw)

100Y 编号	厂商编号	制造厂商	说明	Output Volt./Current	Tol.(±)
31877	ESC-120-13.5	MEAN WELL	MEAN WELL_108W Desktop Power Supply or Charger	13.5V/0~8A	±2%
31879	ESC-120-27	MEAN WELL	MEAN WELL_108W Desktop Power Supply or Charger	27V/0~4A	±1%
31880	ESC-120-54	MEAN WELL	MEAN WELL_108W Desktop Power Supply or Charger	54V/0~2A	±1%
17837	ESC-240-13.5	MEAN WELL	MEAN WELL_216W Desktop Power Supply/Charger	13.5V/16A	±2%
17836	ESC-240-27	MEAN WELL	MEAN WELL_216W Desktop Power Supply/Charger	27V/8A	±1%
21145	ESC-240-54	MEAN WELL	MEAN WELL_216W Desktop Power Supply/Charger	54V/4A	±2%
31881	ESP-120-13.5	MEAN WELL	MEAN WELL_108W Desktop Power Supply or Charger	13.5V/0~8A	±2%
31882	ESP-120-27	MEAN WELL	MEAN WELL_108W Desktop Power Supply or Charger	27V/0~4A	±1%
31883	ESP-120-54	MEAN WELL	MEAN WELL_108W Desktop Power Supply or Charger	54V/0~2A	±1%
21146	ESP-240-13.5	MEAN WELL	216W Desktop Power Supply/Charger	13.5V/16A	±2%
17882	ESP-240-27	MEAN WELL	216W Desktop Power Supply/Charger	27V/8A	±1%
21148	ESP-240-54	MEAN WELL	216W Desktop Power Supply/Charger	54V/4A	±1%

## 55W~250W 可充电-双组电源供应器

详细产品规格 - 请点击 [cn.100y.com.tw](http://cn.100y.com.tw)



**特点:**

- 普遍AC被输入/全方位
- 固定激活PFC作用, PF>0.95
- 保护: 短路/OLP/OVP
- 电池电量低和电池极性保护
- 冷却由自由空气对流
- 100% 全负荷留下消耗测试
- 固定的开关频率在 PFC 67KHz,
- PWM 134KHz
- 2年保单

输入电压范围: 88 ~ 264VAC 124 ~ 370VDC  
 AC 电流: 2.5A/115VAC 1.5A/230VAC  
 流入电流 (max.): 冷起动20A/115VAC 40A/230VAC

漏电: <1mA/ 240VAC  
 运作的温度: -10 ~ +60°C(参见产品装载减税曲线)  
 安全标准: UL60950-1,TUV EN60950-1Approved  
 承受电压: I/P-O/P:3KVAC I/P-FG:1.5KVAC



O/P-FG:0.5KVAC  
 直径: 199\*110\*50mm (L\*W\*H)



100Y 编号	厂商编号	制造厂商	说明	Output Volt./Current	Tol.(±)	Output Volt./Current	Tol.(±)	Output Volt./Charger
30475	ADD-155A	MEAN WELL	MEAN WELL_155W 可充电-双组电源供应器(UPS function)	5V/0.0~3.00A	±3%	13.8V/0.0~10.5A	±2%	13.3V/0.0~0.50A
30497	ADD-155B	MEAN WELL	MEAN WELL_155W 可充电-双组电源供应器(UPS function)	5V/0.0~3.00A	±3%	27.6V/0.0~5.00A	±1%	27.1V/0.0~0.50A
30498	ADD-155C	MEAN WELL	MEAN WELL_155W 可充电-双组电源供应器(UPS function)	5V/0.0~3.00A	±5%	54.0V/0.0~2.50A	±1%	53.5V/0.0~0.20A



**特点:**

- 普遍AC被输入/全方位
- 保护: 短路/OLP/OVP
- 电池电量低保护
- 冷却由自由空气对流
- 100% 全负荷留下消耗测试
- 固定的开关频率在 45KHz
- 2年保单

输入电压范围: 88 ~ 264VAC 124 ~ 370VDC  
 AC 电流: 1.6A/115VAC 1A/230VAC  
 流入电流 (max.): 冷起动20A/115VAC 40A/230VAC  
 漏电: <1mA/ 240VAC

运作的温度: -10 ~ +60°C(参见产品装载减税曲线)  
 安全标准: UL60950-1,TUV EN60950-1Approved  
 承受电压: I/P-O/P:3KVAC I/P-FG:1.5KVAC



O/P-FG:0.5KVAC  
 直径: 159\*97\*38mm (L\*W\*H)

100Y 编号	厂商编号	制造厂商	说明	Output Volt./Current	Tol.(±)	Output Volt./Current	Tol.(±)	Output Volt./Charger
30464	ADD-55A	MEAN WELL	MEAN WELL_55W 可充电-双组电源供应器(UPS function)	5V/0.0~4.00A	±3%	13.8V/0.0~3.50A	±1%	13.4V/0.0~0.23A
30466	ADD-55B	MEAN WELL	MEAN WELL_55W 可充电-双组电源供应器(UPS function)	5V/0.0~4.00A	±3%	27.6V/0.0~2.00A	±1%	26.5V/0.0~0.16A

## 其他交换式电源供应器

详细产品规格 - 请点击 [cn.100y.com.tw](http://cn.100y.com.tw)



**特点:**

- 小规格, 大功率密度
- 低成本, 高可靠性
- 105°C产品电容器。
- 100% 全负荷烧灼测试。
- 普遍AC输入范围
- 修造在EMI过滤器里, 低波纹噪声。
- 高效率, 低运作的温度。
- 软起动电路, 限制AC冲击电流。
- 短路, 超载, 过电压被保护

输入电压范围: : 88 ~ 264VAC 47~63Hz 124 ~ 370VDC  
 AC 电流: 2.5A/115VAC 1.5A/230VAC  
 流入电流 (max.): 冷起动 20A/115VAC 40A/230VAC  
 漏电: <1mA/ 240VAC  
 运作的温度湿度: -10 ~ +60°C(参见产品装载减税曲线)20%~90% RH  
 安全标准: UL1950,TUV EN60950 Approved  
 承受电压: I/P-O/P:3KVAC I/P-FG:1.5KVAC  
 O/P-FG:0.5KVAC  
 直径: 199\*110\*50mm CASE: 906

100Y 编号	厂商编号	制造厂商	说明	Output Volt./Current	Tol.(±)	Output Volt./Current	Tol.(±)
21091	ADS-15512	MEAN WELL	MEAN WELL_155W Single Output with 5V/3A DC-DC Converter	12V/0~12.5A	±2%	5V/0~3.0A	±3%
13757	ADS-15524	MEAN WELL	MEAN WELL_155W Single Output with 5V/3A DC-DC Converter	24V/0~6.5A	±1%	5V/0~3.0A	±3%
21092	ADS-15548	MEAN WELL	MEAN WELL_155W Single Output with 5V/3A DC-DC Converter	48V/0~3.2A	±1%	5V/0~3.0A	±5%



服务专线: 台湾: 886-3-5753170

传 真: 台湾: 886-3-5753172

E-mail: 台湾: sale@100y.com.tw

深圳: 86-755-83298787

深圳: 86-755-83640655

深圳: 100y@163.com

上海: 86-21-34970699

上海: 86-21-64605107

上海: 100y-1@163.com