

# 继电器+电磁阀


## MK\_系列8角和11角继电器 OMRON\_MK2P-I 8角圆形继电器

详细产品规格 - 请点击 [cn.100y.com.tw](http://cn.100y.com.tw)




- 格外可靠的通用继电器
- 由银色触点保证寿命长(极小值100,000 电子操作)
- 固定操作显示(机械, LED), 二极管浪涌镇压, 变阻器浪涌镇压
- 触电操作可能由机械显示容易地检查并且/或者推挤对测试按钮选择
- 依照 CENELEC 标准
- VDE 认证可行

MK2P-I, S  
Standard type (AC/DC coil)



### CHARACTERISTICS

触点电阻	50 m max.	
动作时间	AC: 20 ms max. DC: 30 ms max.	
释放时间	20 ms max.	
操作频率	Mechanical	18,000 operations/hour
	Electrical	1,800 operations/hour (under rated load)
绝缘电阻	100 M min. (at 500 VDC)	
振动	Mechanical durability	10 to 55 Hz, 1.50 mm (0.06 in) double amplitude
	Malfunction durability	10 to 55 Hz, 1.00 mm (0.04 in) double amplitude
冲击	Mechanical durability	1,000 m/s <sup>2</sup> (approx. 100 G)
	Malfunction durability	100 m/s <sup>2</sup> (approx. 10 G)
四周温度	Operation: -10 to 40°C (14 to 104°F)	
四周湿度	35 to 85% RH	
寿命	Mechanical	10 million operations min. (at operating frequency of 18,000 operations/hour)
	Electrical	100,000 operations at rated load (at operating frequency of 1,800 operations/hour)
重量	Approx. 0.85 g (3.0 oz)	




100Y 编号	厂商编号	制造厂商	说明	Contact form	Coil rating	Contact rating
4338	MK2P-I-AC110V	OMRON	8 角圆形继电器	DPDT	110Vac	250Vac,28Vdc/ 10A
4867	MK2P-I-AC220V	OMRON	8 角圆形继电器	DPDT	220Vac	250Vac,28Vdc/ 10A
37245	MK2P-I-DC12VDC	OMRON	OMRON MK 型 控制盘用 电源继电器	2C	12VDC	5A 24VDC/5A 240VAC
4337	MK2P-I-DC24V	OMRON	8 角圆形继电器	DPDT	24Vdc	250Vac,28Vdc/ 10A

## OMRON\_MK3P-I 11角圆形继电器

详细产品规格 - 请点击 [cn.100y.com.tw](http://cn.100y.com.tw)





- 格外可靠的通用继电器
- 由银色触点保证寿命长(极小值100,000 电子操作)
- 固定操作显示(机械, LED), 二极管浪涌镇压, 变阻器浪涌镇压
- 触电操作可能由机械显示容易地检查并且/或者推挤对测试按钮选择
- 依照 CENELEC 标准
- VDE 认证可行



### CHARACTERISTICS

触点电阻	50 m max.	
动作时间	AC: 20 ms max. DC: 30 ms max.	
释放时间	20 ms max.	
操作频率	Mechanical	18,000 operations/hour
	Electrical	1,800 operations/hour (under rated load)
绝缘电阻	100 M min. (at 500 VDC)	
振动	Mechanical durability	10 to 55 Hz, 1.50 mm (0.06 in) double amplitude
	Malfunction durability	10 to 55 Hz, 1.00 mm (0.04 in) double amplitude
冲击	Mechanical durability	1,000 m/s <sup>2</sup> (approx. 100 G)
	Malfunction durability	100 m/s <sup>2</sup> (approx. 10 G)
四周温度	Operation: -10 to 40°C (14 to 104°F)	
四周湿度	35 to 85% RH	
寿命	Mechanical	10 million operations min. (at operating frequency of 18,000 operations/hour)
	Electrical	100,000 operations at rated load (at operating frequency of 1,800 operations/hour)
重量	Approx. 0.85 g (3.0 oz)	



MK3P5-1, -S  
Standard type (AC/DC coil)

100Y 编号	厂商编号	制造厂商	说明	Contact form	Coil rating	Contact rating
12786	MK3P-I-24VAC		11 Pins Coil 继电器	3PDT	24VAC	250Vac,28Vdc/10A
4869	MK3P-I-AC110V	OMRON	11 Pins Coil 继电器	3PDT	110Vac	250Vac,28Vdc/10A
4870	MK3P-I-AC220V	OMRON	11 Pins Coil 继电器	3PDT	220Vac	250Vac,28Vdc/10A
12473	MK3P-I-DC12V	OMRON	11 Pins Coil 继电器	3PDT	12Vdc	250Vac,28Vdc/10A
4868	MK3P-I-DC24V	OMRON	11 Pins Coil 继电器	3PDT	24Vdc	250Vac,28Vdc/10A

<http://cn.100y.com>

# 胜特力电子目录



服务专线: 台湾: 886-3-5753170  
传 真: 台湾: 886-3-5753172  
E-mail: 台湾: sale@100y.com.tw

深圳: 86-755-83298787  
深圳: 86-755-83640655  
深圳: 100y@163.com

上海: 86-21-34123367 & 54151736 29-139  
上海: 86-21-64605107  
上海: 100y-1@163.com