

二极管+电晶体+模块

矽整流二极管

详细产品规格 - 请点击 cn.100y.com.tw

DO-15

Dim	Min	Max
A	25.4	—
B	5.50	7.62
C	0.71	0.864
D	2.60	3.80

All Dimensions in mm

AXIAL LEAD CASE 59-10 ISSUE S

INCHES		MILLIMETERS		
DIM	MIN	MAX	MIN	MAX
A	0.181	0.205	4.10	5.20
B	0.079	0.106	2.00	2.70
D	0.028	0.034	0.71	0.86
F	—	0.050	—	1.27
K	1.000	—	25.40	—

AXIAL LEAD CASE 267-05 ISSUE G

INCHES		MILLIMETERS		
DIM	MIN	MAX	MIN	MAX
A	0.287	0.373	7.30	9.50
B	0.189	0.209	4.80	5.30
D	0.047	0.051	1.20	1.30
K	1.000	—	25.40	—

DO-201AD

DO-201AD		
Dim	Min	Max
A	25.4	—
B	8.50	9.50
C	1.20	1.30
D	5.0	5.60

All Dimensions in mm

DO-35

AXIAL LEAD BUTTON CASE 194-04 ISSUE H

INCHES		MILLIMETERS		
DIM	MIN	MAX	MIN	MAX
A	0.332	0.342	8.43	8.69
B	0.234	0.246	5.94	6.25
D	0.050	0.053	1.27	1.35
K	0.990	1.010	25.15	25.65

100Y 编号	厂商编号	制造厂商	说明	Iav (A)	Pins/Package	Vrrm
24070	1N4006	ON-Semi.	Axial Lead Standard Recovery Rectifier	30A	Axial Lead	800V
8478	1N5392	LITE-ON	General Purpose Rectifier	1.5A	DO-15	100V
8479	1N5397		General purpose plastic rectifier	1.5A	DO-15	600V
7750	1N5402	LITE-ON	Standard Recovery Rectifier	3A	DO-201AD	200V
23169	1N5402-TB		SILICON RECTIFIER	200A	DO-201AD	200V
8477	1N5404		Standard Recovery Rectifier	3A	DO-201AD	400V
8127	1N5408	LITE-ON	General Purpose Plastic Rectifiers	3A	DO-201AD	1000V
49279	1N965B	POWER INT.	FAIRCHILD 二极管		DO-35	
40907	BAT54WS	PANJIT	PHOTON COUPLED ISOLATOR Ga As INFRARED EMITTING DIODE & LIGHT ACTIVATED SCR	60mA	SMD	1.5V
22501	BY255/T		MEDIUM CURRENT PLASTIC RECTIFIER	100Amps	DO-201AD	1300V
45040	D3SB60		矽整流二极管	4A	CASE	600V
8480	LT6A04	LITE-ON	Plastic silicon rectifier	6A	R-6	400V
35480	MR750	ON-Semi.	High Current Lead Mounted Rectifiers	6.0A	Axial Lead	50V
35481	MR751	ON-Semi.	High Current Lead Mounted Rectifiers	6.0A	Axial Lead	100V
35482	MR752	ON-Semi.	High Current Lead Mounted Rectifiers	6.0A	Axial Lead	200V
35483	MR754	ON-Semi.	High Current Lead Mounted Rectifiers	6.0A	Axial Lead	400V
23427	MR756	MOTOROLA	High Current Lead Mounted Rectifiers	6A	194-04	600V
23999	SM4004		Passivated Rectifier (Pb Free)	1A	DO-213AB	400Vrrm

DACO 快速回复二极管

详细产品规格 - 请点击 cn.100y.com.tw

DO-204AL (DO-41)

0.107 (2.7)
0.080 (2.0)
DIA.

1.0 (25.4)
MIN.

0.205 (5.2)
0.160 (4.1)

0.034 (0.86)
0.028 (0.71)
DIA.

1.0 (25.4)
MIN.

DO-204AC (DO-15)

0.140 (3.6)
0.104 (2.6)
DIA.

1.0 (25.4)
MIN.

0.300 (7.6)
0.230 (5.8)

0.034 (0.86)
0.028 (0.71)
DIA.

1.0 (25.4)
MIN.



100Y 编号	厂商编号	制造厂商	说明	Vrrm	Io (A)	Trr (nS)	Pins/Package
24515	1N4933	DACO	DACO_1.0A Silicon Rectifier	50V	1.0A	150nS	DO-41
24215	1N4933G	DACO	DACO_1.0A Fast Recovery Rectifier	50V	1.0A	200nS	DO-41
24516	1N4934	DACO	DACO_1.0A Silicon Rectifier	100V	1.0A	150nS	DO-41
24216	1N4934G	DACO	DACO_1.0A Fast Recovery Rectifier	100V	1.0A	200nS	DO-41
24517	1N4935	DACO	DACO_1.0A Silicon Rectifier	200V	1.0A	150nS	DO-41
24217	1N4935G	DACO	DACO_1.0A Fast Recovery Rectifier	200V	1.0A	200nS	DO-41
24518	1N4936	DACO	DACO_1.0A Silicon Rectifier	400V	1.0A	150nS	DO-41



服务专线: 台湾: 886-3-5753170

传 真: 台湾: 886-3-5753172

E-mail: 台湾: sale@100y.com.tw

深圳: 86-755-83298787

深圳: 86-755-83640655

深圳: 100y@163.com

上海: 86-21-34970699

上海: 86-21-64605107

上海: 100y-1@163.com