

二极管+电晶体+模块

DACO_Button Devices-回复二极管

详细产品规格 - 请点击 cn.100y.com.tw

100Y 编号	厂商编号	制造厂商	说明	V _{rrm}	I _o (A)	Package
26800	ARS5001	DACO	50A Button_Silicon Rectifier	50V	50A	ARS
26755	ARS5001G	DACO	50A Button_Glass Passivated Rectifier	50V	50A	ARS
26801	ARS5002	DACO	50A Button_Silicon Rectifier	100V	50A	ARS
26756	ARS5002G	DACO	50A Button_Glass Passivated Rectifier	100V	50A	ARS
26802	ARS5003	DACO	50A Button_Silicon Rectifier	200V	50A	ARS
26757	ARS5003G	DACO	50A Button_Glass Passivated Rectifier	200V	50A	ARS
26803	ARS5004	DACO	50A Button_Silicon Rectifier	400V	50A	ARS
26758	ARS5004G	DACO	50A Button_Glass Passivated Rectifier	400V	50A	ARS
26804	ARS5005	DACO	50A Button_Silicon Rectifier	600V	50A	ARS
26759	ARS5005G	DACO	50A Button_Glass Passivated Rectifier	600V	50A	ARS
26805	ARS5006	DACO	50A Button_Silicon Rectifier	800V	50A	ARS
26760	ARS5006G	DACO	50A Button_Glass Passivated Rectifier	800V	50A	ARS
26806	ARS5007	DACO	50A Button_Silicon Rectifier	1000V	50A	ARS
26761	ARS5007G	DACO	50A Button_Glass Passivated Rectifier	1000V	50A	ARS

快速回复二极管

详细产品规格 - 请点击 cn.100y.com.tw

DO-205AA (DO-8)

ACROSS FLATS
3/8" -24UNF-2A

DO-203AA (DO-41)

10/32" UNF-2A
For metric devices: M5x0.8

AXIAL LEAD
CASE 59-10 ISSUE S

DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.161	0.205	4.10	5.20
B	0.079	0.106	2.00	2.70
D	0.028	0.034	0.71	0.86
F	—	0.050	—	1.27
K	1.000	—	25.40	—

AXIAL LEAD
CASE 267-05 ISSUE G

DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.237	0.374	7.30	9.50
B	0.189	0.209	4.80	5.30
D	0.047	0.051	1.20	1.30
K	1.000	—	25.40	—

DO-205AC (DO-30)

1/2" -20UNF-2A

D²Pak (SMD-220)

MINIMUM RECOMMENDED FOOTPRINT

100Y 编号	厂商编号	制造厂商	说明	Pins/Package	V _{rrm}	I _F (A)	T _{rr} (nS)
35460	150K40A	IR	STANDARD RECOVERY DIODES	DO-205AA	400V	150A	-40 to 200
35512	150KR20A	IR	STANDARD RECOVERY DIODES	DO-205AA	200V	235A	
35516	150KR40A	IR	STANDARD RECOVERY DIODES	DO-205AA	400V	235A	
35530	16F120	IR	STANDARD RECOVERY DIODES	DO-203AA	1200V	25A	
35596	16FR120	IR	STANDARD RECOVERY DIODES	DO-203AA	1200V	16A	
35600	16FR80	IR	STANDARD RECOVERY DIODES	DO-203AA	800V	16A	
23168	1N4934	MOTOROLA	Axial-Lead Fast-Recovery Rectifier	DO-41	100V	30A	200ns
48236	UF4004	Micro-semi	ULTRAFast EFFICIENT PLASTIC RECTIFIER	DO-41	400V	1.0A	50ns
42568	1N5916B		1.5W SILICON ZENER DIODE	DO-41			
35664	200HF120PV	IR	STANDARD RECOVERY DIODES	DO-205AC (DO-30)	1200V	200A	
35667	20ETF06S	IR	SURFACE MOUNTABLE FAST SOFT RECOVERY RECTIFIER DIODE	D2 Pak (SMD-220)	600V	300A	60ns
35484	MR852	ON-Semi.	Axial Lead Fast Recovery Rectifiers	Axial Lead	200V	3.0A	200ns
35486	MR856	ON-Semi.	Axial Lead Fast Recovery Rectifiers	Axial Lead	600V	3.0A	200ns
42358	MUL460RL	ON-Semi.	SWITCHMODE Power Rectifiers	Axial Lead	600V	4A	
42350	MUR2100ERLG		Ultrafast Rectifier	Axial Lead	1000V	2A	
42357	MUR4100EG	ON-Semi.	SWITCHMODE Power Rectifiers	Axial Lead	1000V	4A	
8489	PR1507S	LITE-ON	fast switching for high efficiency	DO-41	1000V	1.5A	500ns