




二极管+电晶体+模块

DACO_穿透式二极管

详细产品规格 - 请点击 cn.100y.com.tw

100Y 编号	厂商编号	制造厂商	说明	Vrrm	Io (A)	Ifsm (A)	Package
26645	PFBM2507(R)	DACO	DACO_SILICONRECTIFIER	1000	25	400	BOSCH(M TYPE)
26646	PFBM3501(R)	DACO	DACO_SILICONRECTIFIER	500	35	600	BOSCH(M TYPE)
26647	PFBM3502(R)	DACO	DACO_SILICONRECTIFIER	100	35	600	BOSCH(M TYPE)
26648	PFBM3503(R)	DACO	DACO_SILICONRECTIFIER	200	35	600	BOSCH(M TYPE)
26649	PFBM3504(R)	DACO	DACO_SILICONRECTIFIER	400	35	600	BOSCH(M TYPE)
26650	PFBM3505(R)	DACO	DACO_SILICONRECTIFIER	600	35	600	BOSCH(M TYPE)
26651	PFBM3506(R)	DACO	DACO_SILICONRECTIFIER	800	35	600	BOSCH(M TYPE)
26652	PFBM3507(R)	DACO	DACO_SILICONRECTIFIER	1000	35	600	BOSCH(M TYPE)
26653	PFBM5001(R)	DACO	DACO_SILICONRECTIFIER	50	50	800	BOSCH(M TYPE)
26654	PFBM5002(R)	DACO	DACO_SILICONRECTIFIER	100	50	800	BOSCH(M TYPE)
26656	PFBM5003(R)	DACO	DACO_SILICONRECTIFIER	200	50	800	BOSCH(M TYPE)
26657	PFBM5004(R)	DACO	DACO_SILICONRECTIFIER	400	50	800	BOSCH(M TYPE)
26658	PFBM5005(R)	DACO	DACO_SILICONRECTIFIER	600	50	800	BOSCH(M TYPE)
26659	PFBM5006(R)	DACO	DACO_SILICONRECTIFIER	800	50	800	BOSCH(M TYPE)
26660	PFBM5007(R)	DACO	DACO_SILICONRECTIFIER	1000	50	800	BOSCH(M TYPE)



DIM	DIMENSIONS				NOTE
	INCHES		MM		
	MIN	MAX	MIN	MAX	
A	0.834	0.857	21.19	21.78	
B	0.336	0.343	8.53	8.70	
C	0.398	0.400	10.11	10.16	
D	0.050	0.051	1.29	1.30	



100Y 编号	厂商编号	制造厂商	说明	Vrrm	Io (A)	Ifsm (A)	Package
26597	PFL2501(R)	DACO	DACO INDUSTRIAL PRESS-FIT POWER RECTIFIER	50	25	400	LUCAS
26598	PFL2502(R)	DACO	DACO INDUSTRIAL PRESS-FIT POWER RECTIFIER	100	25	400	LUCAS
26599	PFL2503(R)	DACO	DACO INDUSTRIAL PRESS-FIT POWER RECTIFIER	200	25	400	LUCAS
26600	PFL2504(R)	DACO	DACO INDUSTRIAL PRESS-FIT POWER RECTIFIER	400	25	400	LUCAS
26601	PFL2505(R)	DACO	DACO INDUSTRIAL PRESS-FIT POWER RECTIFIER	600	25	400	LUCAS
26602	PFL2506(R)	DACO	DACO INDUSTRIAL PRESS-FIT POWER RECTIFIER	800	25	400	LUCAS
26603	PFL2507(R)	DACO	DACO INDUSTRIAL PRESS-FIT POWER RECTIFIER	1000	25	400	LUCAS
26604	PFL3501(R)	DACO	DACO INDUSTRIAL PRESS-FIT POWER RECTIFIER	50	35	600	LUCAS
26605	PFL3502(R)	DACO	DACO INDUSTRIAL PRESS-FIT POWER RECTIFIER	100	35	600	LUCAS
26606	PFL3503(R)	DACO	DACO INDUSTRIAL PRESS-FIT POWER RECTIFIER	200	35	600	LUCAS
26607	PFL3504(R)	DACO	DACO INDUSTRIAL PRESS-FIT POWER RECTIFIER	400	35	600	LUCAS
26608	PFL3505(R)	DACO	DACO INDUSTRIAL PRESS-FIT POWER RECTIFIER	600	35	600	LUCAS
26609	PFL3506(R)	DACO	DACO INDUSTRIAL PRESS-FIT POWER RECTIFIER	800	35	600	LUCAS
26610	PFL3507(R)	DACO	DACO INDUSTRIAL PRESS-FIT POWER RECTIFIER	1000	35	600	LUCAS
26611	PFL5001(R)	DACO	DACO INDUSTRIAL PRESS-FIT POWER RECTIFIER	50	50	800	LUCAS
26612	PFL5002(R)	DACO	DACO INDUSTRIAL PRESS-FIT POWER RECTIFIER	100	50	800	LUCAS
26613	PFL5003(R)	DACO	DACO INDUSTRIAL PRESS-FIT POWER RECTIFIER	200	50	800	LUCAS
26614	PFL5004(R)	DACO	DACO INDUSTRIAL PRESS-FIT POWER RECTIFIER	400	50	800	LUCAS
26615	PFL5005(R)	DACO	DACO INDUSTRIAL PRESS-FIT POWER RECTIFIER	600	50	800	LUCAS
26616	PFL5006(R)	DACO	DACO INDUSTRIAL PRESS-FIT POWER RECTIFIER	800	50	800	LUCAS
26617	PFL5007(R)	DACO	DACO INDUSTRIAL PRESS-FIT POWER RECTIFIER	1000	50	800	LUCAS

桥式/三相整流器 DIP/圆形-桥式整流器

详细产品规格 - 请点击 cn.100y.com.tw

**AXIAL LEAD, DO-41
CASE 59-10 ISSUE S**

DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.161	0.205	4.10	5.20
B	0.079	0.106	2.00	2.70
D	0.028	0.034	0.71	0.86
F	-	0.050	-	1.27
K	1.000	-	25.40	-

DO-67

LUG TERMINAL ANODE
BASE CATHODE

TO-220AB

DIM	DIMENSIONS				NOTE
	INCHES		MM		
	MIN	MAX	MIN	MAX	
A	.560	.625	14.22	15.88	
B	.380	.420	9.65	10.67	
C	.100	.135	2.54	3.43	
D	.230	.270	5.84	6.86	
E	.380	.420	9.65	10.67	
F	-	.250	-	6.35	
G	.500	.580	12.70	14.73	
H	.090	.110	2.29	2.79	
I	.020	0.045	0.51	1.14	
J	.012	0.025	0.30	0.64	
K	.139	.161	3.53	4.09	Φ
L	.140	.190	3.56	4.83	
M	.045	.055	1.14	1.40	
N	.080	.115	2.03	2.92	



服务专线: 台湾: 886-3-5753170

深圳: 86-755-83298787

上海: 86-21-34970699

传 真: 台湾: 886-3-5753172

深圳: 86-755-83640655

上海: 86-21-64605107

E-mail: 台湾: sale@100y.com.tw

深圳: 100y@163.com

上海: 100y-1@163.com