



# 二极管+电晶体+模块

## 平躺式桥式整流器

详细产品规格 - 请点击 [cn.100y.com.tw](http://cn.100y.com.tw)

100Y 编号	厂商编号	制造厂商	说明	Vrrm	IF (A)	Package
39649	GBPC2510W		Glass Passivated Bridge Rectifier.	1000V	25A	GBPC-W
8130	BR108		插板式桥式整流器	800V	10A	BR-10
8132	KBPC806	LITE-ON	插板式桥式整流器	600V	8A	PBPC-8(BR-10)
7742	PBPC605	LITE-ON	插板式桥式整流器	600V	6A	PBPC-6

## 三相整流器

详细产品规格 - 请点击 [cn.100y.com.tw](http://cn.100y.com.tw)

**12-46A1A**  
Dimensions: 15.5±0.3, 15.5±0.3, 4.5, 5.5 MAX, 27.5 MAX, 19.0 MIN, 7.8 MAX, 18.2, 46.2 MAX, 7.6, 7.6, 2.4, 1.1, 5 MAX, 14.5±0.3, 6.3x.8(.25x.03), 10, 23(.90), 21(.83), 25.3(.99) MAX, 16(.63), 5.2(.20), 28.5(.12).

**D-63**  
Suggested plugging force: 400N max; axially applied to faston terminals.  
All dimensions in millimeters (inches).

**70MT160KB**  
Screws M5x0.8 length 10.  
Dimensions: 25.5±0.5 (1.00±0.02), 3.0±0.5 (1.17±0.02), 3.8±0.5 (1.50±0.02), 8.5±0.5 (0.34±0.02), 3.5±0.3 (1.38±0.01).  
All dimensions in millimeters (inches).

**DF60AA120**  
5-M5.  
Dimensions: 16.5±0.3 (0.71±0.01), 4.6±0.3 (1.81±0.01), 8.0±0.3 (3.15±0.01), 9.4±0.3 (3.70±0.01), 14.0±0.3 (0.55±0.01).

**DF75BA80**  
NAME PLATE.  
Dimensions: 18±0.3 (0.71±0.01), 4.6±0.3 (1.81±0.01), 8.0±0.3 (3.15±0.01), 9.4±0.3 (3.70±0.01), 14.0±0.3 (0.55±0.01).

100Y 编号	厂商编号	制造厂商	说明	Vrrm	IF (A)	Package
35424	110MT160K	IR	THREE PHASE BRIDGE	1600A	950A	5-Lead Molded
35742	160MT80KB	IR	THREE PHASE BRIDGE	800V	160A	
16474	20L6P45	TOSHIBA	三相整流器	800V	20A	12-46A1A
35731	26MT120	IR	THREE PHASE BRIDGE	1200V	25A	D-63
35732	26MT160	IR	THREE PHASE BRIDGE	1600V	25A	D-63
35733	26MT60	IR	THREE PHASE BRIDGE	600V	25A	D-63
35734	26MT80	IR	THREE PHASE BRIDGE	800V	25A	D-63
16507	30G6P41	TOSHIBA	三相整流器	1000V	30A	
36129	36MT100	IR	THREE PHASE BRIDGE	1000V	35A	
36128	36MT120	IR	THREE PHASE BRIDGE	1200V	35A	
28438	36MT160	IR	三相桥整流器	160V	35A	5-Lead Molded
36124	36MT80	IR	THREE PHASE BRIDGE	800V	35A	
35660	70MT160KB	IR	THREE PHASE BRIDGE	1600V	60A	
16644	DF60AA120	SanRex	SanRex_DIODE 模组	1200V	60A	
42832	DF75AA160	SanRex	DIODE 模组	1600V	75A	
32196	DF75BA80	SanRex	DIODE 模组	800V	75A	

## 瞬间电压抑制二极管(TVS)

### 1.5KE\_瞬变电压抑制二极管(TVS)

详细产品规格 - 请点击 [cn.100y.com.tw](http://cn.100y.com.tw)

**Case style 1.5KE**  
Dimensions: 0.210 (5.3) DIA., 0.190 (4.8) DIA., 1.0 (25.4) MIN., 0.375 (9.5) / 0.285 (7.2), 0.042 (1.07) / 0.038 (0.96) DIA., 1.0 (25.4) MIN.

**DO-201**  
Dimensions: B, A, B, ΦD, ΦC.

REF.	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	8.5		9.5	0.335		0.374
B	25.4		1			
ΦC	4.8		5.3	0.189		0.209
ΦD	0.96		1.06	0.036		0.042

**DO-201AE**  
Dimensions: 0.210 (5.3) / 0.188 (4.8) DIA., 1.0 (25.4) MIN., 0.375 (9.5) / 0.285 (7.2), 0.042 (1.07) / 0.037 (0.94) DIA., 1.0 (25.4) MIN.

**MOSORB CASE 41A-04 ISSUE D**

DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.335	0.374	8.50	9.50
B	0.189	0.209	4.80	5.30
D	0.038	0.042	0.96	1.06
K	1.000	---	25.40	---
P	---	0.050	---	1.27

100Y 编号	厂商编号	制造厂商	说明	Power (W)	Stand-off Vrrm	Vbr min	Vbr max	单/双向	Package
35366	1.5KE400A	ON-Semi.	TRANSZORB TRANSIENT VOLTAGE SUPPRESSOR	1500W	342V	360V	420V	UNDIRECTIONAL	DO-15



服务专线: 台湾: 886-3-5753170

传 真: 台湾: 886-3-5753172

E-mail: 台湾: sale@100y.com.tw

深圳: 86-755-83298787

深圳: 86-755-83640655

深圳: 100y@163.com

上海: 86-21-34970699

上海: 86-21-64605107

上海: 100y-1@163.com