


晶体+IC座/夹

PLCC Burn-In/测试座

详细产品规格 - 请点击 cn.100y.com.tw



Item No. IS0003-P32 (Clam shell)
 Page No. 6165
 IC SIZE: 12.3x14.9
 Pitch: 1.27
 Remark: socket name: IC51-0324-453
 Specification: PLCC32pin.

100Y 编号	厂商编号	制造厂商	说明	Pins/Pitch
11653	PLCC32DIP-32-Y	YAMAICHI	YAMAICHI PLCC	PLCC 32Pins
16155	PLCC32PIN453PCB		PLCC-32PIN 上板+下板(IC51-0324-453 PCB)	32P

SOP/SSOP/TSOP Burn-In/测试座

详细产品规格 - 请点击 cn.100y.com.tw

A08-0032-17

FP-16-0.65-01

FP-16-1.27-05

A-40-1174
(2100mil) 53.34mm

04334-121-6215

656-1082211

100Y 编号	厂商编号	制造厂商	说明	Pins/Pitch	适用 IC 包装
14840	04334-121-6215		SOT-26 转接座	26P	
14008	656-1082211	WELLS-CTI	SOP-8 脚座-Mini SOP-8 Package Wells		
17046	A-40-1174		For:IC51-0402-1174 PCB		
17640	A08-0032-17		TSOP-28 Tester Socket	TSOP-28	
12568	FP-16-0.65-01	ENPLAS	烧录 IC 转接座		
30877	FP-16-1.27-05	ENPLAS	掀盖式 转接座	16P/1.27	SOP

FP-20-0.65-01A

FP-24-1.27-08

FP-20-1.27-06

FP-28-1.27-07

FP-28-1.27-08A

特点:

接点电阻: Initial 30m or 50m (At 10mA)
 最大电压: AC700V RMS (for 1 minute)
 * Below 0.5mm Pitch
 AC500V RMS (for 1 minute)

绝缘电阻: 1,000Mor higher (At DC 500V)
 电流规定值: 1A
 终端反拉力: 0.5kg (1 minute)
 绝缘体: Min. 10,000 times (Mechanical)
 操作温度范围: -60C ~ +150C

材质:

Body: PEI, PES /
 Contact: BeCu,
 SnNiCu, Au plating
 (Ni-base)

100Y 编号	厂商编号	制造厂商	说明	Pins/Pitch	耐温℃	适用 IC 包装
48646	FP-20-0.65-01A	ENPLAS	with Floating 掀盖式 20P 转接座 Pitch:0.65	20P/0.65	-60°C ~ +150°C	
38001	FP-20-1.27-06	ENPLAS	Applicable IC/SOP SOL SSOP TSOP	1.27	-60°C ~ +150°C	
22444	FP-24-1.27-08	ENPLAS	Applicable IC/SOP SOL SSOP TSOP	1.27	-60°C ~ +150°C	SOP
46684	FP-28-1.27-07	ENPLAS	28P-SOP Burn-In Socket	28P-1.27mm	-60-150 °C	SOP
22445	FP-28-1.27-08A	ENPLAS	SOP SOL SSOP TSOP Burn-In Socket	28P-1.27mm	-60-150	SOP



服务专线: 台湾: 886-3-5753170
 传 真: 台湾: 886-3-5753172
 E-mail: 台湾: sale@100y.com.tw

深圳: 86-755-83298787
 深圳: 86-755-83640655
 深圳: 100y@163.com

上海: 86-21-34970699
 上海: 86-21-64605107
 上海: 100y-1@163.com