








## 电感式近接感测元件






详细产品规格 - 请点击 [cn.100y.com.tw](http://cn.100y.com.tw)



IE5082/IEB3001-ANOG IE5107/IEC3002-ANOG IE5202/IE-2002-FROG IE5207/IEB2001-AROG IE5222/IEA2001-FROG

Electrical design	DC NPN	DC NPN	DC PNP/NPN	DC PNP/NPN	DC
输出	normally open	normally open	normally open / closed programmable	normally open	normally open / closed programmable
操作电压	10...36 DC	10...36 DC	5...36 DC	10...36 DC	5...36 DC
电流范围	200	200	200	200	200
短路保护	—	—	—	—	—
反向极性保护/超载保护	—	—	—	—	—
电压降落	< 1	< 1	< 4,6	< 2,6	< 4,6
消耗电流	< 15 (24V)	< 15 (24V)	< 0,8	< 0,8	< 0,8
Real sensing range [mm]	1±10%	2±10%	2±10%	1±10%	1±10%
操作距离	0...0,8	0...1,6	0...1,6	0...0,8	0...0,8
操作温度	-25...+80	-25...+80	-25...+80	-25...+80	-25...+80
保护	IP 67	IP 67	IP 67, III	IP 67	IP 67, III
外壳材料	brass Optalloy-platedPBTP	PBTP	Pocan ARNITEL	brass Optalloy-platedPBTP	brass Optalloy-platedactive face: PBTP
接点	PVC cable / 2m; 3 x 0,14mm <sup>2</sup>	PVC cable / 2m; 3 x 0,14mm <sup>2</sup>	PUR/PVC cable / 2m; 2 x 0,14mm <sup>2</sup>	PVC cable / 2m; 2 x 0,14mm <sup>2</sup>	PUR/PVC cable / 2m; 2 x 0,14mm <sup>2</sup>
接线	Core colours BN brown BU blue BK black				

100Y 编号	厂商编号	制造厂商	说明	Size	Sensing Distance	Output
4851	IE5082/IEB3001-ANOG	IFM	电感式近接开关-Vin:10~36Vdc, DC-3 线输出	M8-金属短型	1mm	NO NPN-No 过载短路保护
4357	IE5107/IEC3002-ANOG	IFM	电感式近接开关-Vin:10~36Vdc, DC-3 线输出	M8-Plastic thread	2mm	NO NPN-No 过载短路保护
4853	IE5202/IE-2002-FROG	IFM	电感式近接开关-Vin:5~36Vdc, DC-2 线输出	M8-Plastic thread	2mm	NO/NC NPN/PNP-No 过载短路保护
14617	IE5207/IEB2001-AROG	IFM	电感式近接开关-动作电压:10~36DC 0.8mA	M8	1mm	DC PNP/NPN
4852	IE5222/IEA2001-FROG	IFM	电感式近接开关-Vin:5~36Vdc, DC-2 线输出	M8-金属型	1mm	NO/NC NPN/PNP-No 过载短路保护



IE5270/IEB21.5-AROG/PH IF5597/IF-2004-FRKG IF5718 IFC2004-ARKG/UP IF5719/IFB2004-ARKG/UP I15272

Electrical design	DC PNP/NPN	DC	DC PNP/NPN	DC PNP/NPN	DC PNP
输出	normally open	normally open / closed programmable	normally open	normally open	normally open
操作电压	5...36 DC	10...55 DC	10...36 DC	10...36 DC	10...36 DC
电流范围	200	400	150	150	250
短路保护	< 4,6	< 4,6	< 4,6	< 4,6	< 2,5
反向极性保护/超载保护	1,5±10%	4±10%	4±10%	4±10%	10±10%
电压降落	0...1,2	0...3,25	0...3,25	0...3,25	0...8,1
消耗电流	0...+60	-25...+80	-25...+80	-25...+80	-25...+80
Real sensing range [mm]	IP 67, III	IP 67	IP 67	IP 67	IP 67
操作距离	EN 60947-5-2; EN 55011 class B	EN 60947-5-2	EN 60947-5-2	EN 60947-5-2; EN 55011 class B	EN 60947-5-2
操作温度	brass nickel-platedPocan	PBTP	PBT	brass nickel-plated CO-PC	PBTP
保护	PUR cable highly flexible / 2m; 2 x 0,14mm <sup>2</sup>	PUR/PVC cable / 2m; 2 x 0,34mm <sup>2</sup>	PVC cable / 2m; 2 x 0,34mm <sup>2</sup>	PVC cable / 2m; 2 x 0,34mm <sup>2</sup>	PVC cable / 2m; 3 x 0,5mm <sup>2</sup>
外壳材料					
接点	Core colours BN brown BU blue BK black				
接线					



服务专线: 台湾: 886-3-5753170  
 传 真: 台湾: 886-3-5753172  
 E-mail: 台湾: sale@100y.com.tw

深圳: 86-755-83298787  
 深圳: 86-755-83640655  
 深圳: 100y@163.com

上海: 86-21-34970699  
 上海: 86-21-64605107  
 上海: 100y-1@163.com