

焊接+除焊+热风产品

Solderite_焊接工具+配件

详细产品规格 - 请点击 cn.100y.com.tw



控制设备

输入电压: SGS-3005/LB3105: AC180-240V, 50/60Hz
 SGS-3015/LB-3115; AC90-125V, 50/60Hz
 耗电: SGS-3005/3015: 20W (average); 120W (max)
 LB-3105/3115: 20W (average); 150W (max)
 Output voltage: DC 0-30V

焊铁

输出功率: SGI-902S: 90W (max)
 LBI-1902S: 130W (max)
 输入电压: DC 0-30V

| 100Y 编号 | 厂商编号 | 说明 | Volt. | 烙铁头长度(mm) | 控温范围 °C | 防静电 Y/N | 输出功率 W | 重量 |
|---------|----------|-------------------|--------|-----------|------------|---------|--------|--------|
| 47370 | SGS-3005 | Solderite_标准型无铅焊台 | AC220V | 145mm | 250-500 °C | Y | 120W | 0.76kg |
| 47371 | SGS-3015 | Solderite_标准型无铅焊台 | AC110V | 145mm | 250-500 °C | Y | 120W | 0.76kg |



控制设备

输入电压: SGS-3505/LB-3605; AC180-240V, 50/60Hz
 SGS-3515/LB-3615; AC90-125V, 50/60Hz
 耗电: SGS-3505/3515: 20W (average); 120W (max)
 LB-3605/3615: 20W (average); 150W (max)
 输出电压: DC 0-33.5V

焊铁

输出功率: SGI-902S: 90W (max)
 LBI-1902S: 130W (max)
 输入电压: DC 0-33.5V

| 100Y 编号 | 厂商编号 | 说明 | Volt. | 烙铁头长度(mm) | 控温范围 °C | 防静电 Y/N | 输出功率 W | 重量 |
|---------|----------|-------------------|--------|-----------|------------|---------|--------|--------|
| 47368 | SGS-3505 | Solderite_数显型无铅焊台 | AC220V | 145mm | 250-500 °C | Y | 120W | 0.76kg |
| 47369 | SGS-3515 | Solderite_数显型无铅焊台 | AC110V | 145mm | 250-500 °C | Y | 120W | 0.76kg |

锡炉+配件

详细产品规格 - 请点击 cn.100y.com.tw



10x20x50Hmm



10x30x50Hmm



155x25x50Hmm



20x52x50Hmm



20x85x50Hmm



30*47*7CM



363



363-3AUTO



52x52x50Hmm



CK-40P

| 100Y 编号 | 厂商编号 | 制造厂商 | 说明 | Consumption W | Supply Volt.(VAC) |
|---------|--------------|------|---------------------|---------------|-------------------|
| 28966 | 10x20x50Hmm | | IC 槽 for 锡炉-10*20mm | | |
| 28967 | 10x30x50Hmm | | IC 槽 for 锡炉-10*30mm | | |
| 48281 | 155x25x50Hmm | | IC 槽 for 锡炉 | | |
| 28968 | 20x52x50Hmm | | IC 槽 for 锡炉-20*52mm | | |
| 28969 | 20x85x50Hmm | | IC 槽 for 锡炉-20*85mm | | |
| 11250 | 30*47*7CM | | 手浸式焊锡炉-方型锡炉/220V | 1.5KW*3 | |
| 6888 | 363-1 | | 6CM 圆型锡炉 | 350W | 110V |
| 6887 | 363-2 | | 8CM 圆型锡炉 | 400W | 110V |
| 6886 | 363-3 | | 10CM 圆型锡炉 | 500W | 110V |
| 47816 | 363-3-220V | | 10CM 圆型锡炉 | 500W | 220V |
| 12573 | 363-3AUTO | K&C | IC 自动控制 温焊锡炉 | 550W | 110V |
| 28970 | 52x52x50Hmm | | IC 槽 for 锡炉-52*52mm | | |
| 11482 | CK-40P | | IC 槽 for 锡炉-21*90mm | | |



FD-162



FD-163

特点:

- 使温度自由地坐在范围约 20-430°C 内
- 做防腐不锈钢
- 操作容易, 散热好和融解速度快
- 它容易修理这个单位和替换辅件

| 100Y 编号 | 厂商编号 | 说明 |
|---------|--------|------------|
| 49876 | FD-162 | 5cm 可调温焊锡炉 |
| 49877 | FD-163 | 8cm 可调温焊锡炉 |



服务专线: 台湾: 886-3-5753170
 传 真: 台湾: 886-3-5753172
 E-mail: 台湾: sale@100y.com.tw

深圳: 86-755-83298787
 深圳: 86-755-83640655
 深圳: 100y@163.com

上海: 86-21-34970699
 上海: 86-21-64605107
 上海: 100y-1@163.com